

SURVEY & REMONUMENTATION
MECOSTA COUNTY REMONUMENTATION PROGRAM
 Corner approved by Peer Group on May 12, 1994
REMONUMENTATION
APR 1 0 1995 AND CORNER RECORDATION CERTIFICATE
 COMMISSIONING
 Enacting Requirement of Act 74, Mich. P.A. 1970

STATE OF MICHIGAN
 COUNTY OF MECOSTA
 RECEIVED FOR RECORD

'94 AUG -3 P 1:38

corners in Mecosta _____ (County) _____
 Committed in: _____ Corner Code # _____

Public Land Survey Sec. T 15 N R 10 W D-13 Big Rapids Township
 Property Controlling _____ T _____ R _____
 in Section _____ T _____ R _____
 Miscellaneous _____ S _____ R _____
 Property in Sec. _____ S _____ R _____

Carl Waldron
 REGISTER OF DEEDS

Register of Deeds Stamp & File Number

Lot No. _____ Recorded Plat _____
 Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Thomas H. Sage a field survey on May 7, 1994
 hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the recent manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as pressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:
 ptember 26, 1937, John Hodgson, Deputy Surveyor, GLO Notes, Volume 2, Pages 222 and 223.

- Set Quarter Section Post
- Beech 8" N65°E 21 links
- Beech 7" N71°W 21 links
- March 26, 1982, Pat Leemon, Surveyor, USFS, Field Notes, Page 4A, 5 and 6
- tabliished corner on Section Line by Single Proportionate Measurement
- ember 17, 1982, Robert A. Griffin, L.S.#13584, LCRC Liber 2, Page 73
- Set 5" x 36" Concrete Monument with Brass Cap
- Pine Post 4" North 32.73 feet
- B. Oak 8" N15°E 64.35 feet
- B. Oak 8" N38°W 68.66 feet

Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 and Standard USFS Monument with Brass Cap 1" below surface and 4 feet +/- North of the Centerline of 12 Mile Road from LCRC Liber 2 Page 73 (Griffin's) witnesses the monument should be approximately 0.2 +/- East of found location. We excavated around monument and discovered it to be leaning to the West. Monument apparently was pushed by a Road Commission truck while grading the roads. We recovered several pieces of broken concrete monument that had been placed around the monument as backfill. The recovered monument was 24" long which was the original length placed. I speculate that when the original monument was placed on March 26, 1982, the road base was still frozen. (The material is a silt/clay.) It appears that the monument was purposely shorter because of the frozen ground.

Set the monument per the witnesses of LCRC Liber 2 page 73.

Set 24" concrete monument with brass cap, 4 feet North of Centerline of 12 Mile Road, 12" +/- below surface.

- Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 and Standard USFS Monument with Brass Cap
- Pine Post 4" North 32.73 feet Spike
 - Black Oak 8" N15°E 64.35 feet Spike
 - Black Oak 8" N38°W 68.66 feet Spike
 - Black Oak 5" S10°E 42.85 feet 60 d Nail with Remonumentation Tag East Side
 - White Oak 30" S20°W 36.92 feet 60 d Nail with Remonumentation Tag East Side

APPROVED BY MECOSTA CO. PEER GROUP
 IN ACCORDANCE WITH P.A. 343 of 1990

James J. Knapp
 CHAIRMAN
 DATE MAY 12, 1994

Monument is accepted as a careful and faithful perpetuation of the position of the original corner.

Witnessed by *John J. Long* Date June 10, 1994

Surveyor's Michigan License No. _____ 33139

