



DELIVERED TO NEWAYGO CO.
01/19/2018 9:57:37 AM



STEWART K. SANDERS
NEWAYGO COUNTY REGISTER OF DEEDS
RECEIVED AND RECORDED
01/19/2018 10:42:08 AM

Land Corner Recordation Certificate
2017 Annual Grant Agreement VOL. 8 238
Authority: MCL 54.205 and R54.202

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2016 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Newaygo County

Corner Type	Survey Township	Corner Code	Goodwell Township																					
			A	B	C	D	E	F	G	H	I	J	K	L	M									
Original Public Land Survey Corner	T 14N R 11W	J05	6	5	4	3	2	1																
• MCL 54.202(g)	T		7	8	9	10	11	12																
• MCL 54.262(g)	T		5				14																	
Property Controlling Corner	S																							
• MCL 54.202(i)	T		18	17	16	15	14	13																
• MCL 54.262(h)	T		19	20	21	22	23	24																
Protracted Public Land Survey Corner	T		30	29	28	27	26	25																
• MCL 54.202(k)	T		31	32	33	34	35	36																
• MCL 54.262(l)	T																							

One Quarter Corner common to Sections 11 and 14, T14N R11W, Goodwell Township, Newaygo County, Michigan.

Part A: Corner History

- GLO
J.H. Mullett, November 22, 1837
Set quarter section post
#1 6" Maple S10°W 17 links (11.22')
#2 8" Maple N61°W 24 links (15.84')

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner

I found a 5/8" x 18" Rerod flush with grade. The corner is online with remnants of a fence to the North. A deer fence to the South is 5'± East. The corner is online with remnant of a fence to the West. A deer fence to the East is 5'± South. The condition of the witnesses are as follows: #1 and #2 gone. Distance from I-5 is 2633.06'. Distance from K-5 is 2517.57'.

Part C: Field Evidence of Perpetuation or Monumentation of Corner

I removed the Rerod and set a 4" diameter Harrison Cast Iron Monument 30" long marked "County Surveyor #22439" to project 4"± above grade and placed stones around monument, as a careful and faithful reestablishment of the position of the original Quarter corner.

- 12" White Oak N42°E 11.52'
- 18" Black Oak North 39.14'
- 22" Black Oak (with blaze) N68°W 16.48'
- 30" Black Oak (with blaze) S73°W 35.95'
- Set 40d nail with tag in Southeast side
- Set 40d nail with tag in East side
- Set 40d nail with tag in North side
- Set 40d nail with tag in Northwest side