

SURVEY & REMONUMENTATION

AUG 0 6 2008

SECTION

Part A continued:

1937 USGLO Dependent Resurvey James T. Boyd and T. Nolan Canada, Transitman, Guy Veal, CE

Mon - The point for the cor. of secs. 17, 18, 19, 20 as determined by the cor. of old fences bearing N. and E., which bears N45°E 71 lks. and by the intersection of old road lines, which bear E and N (The E and W road is on small offset to North at this point, but in line 2.00 chs. East). The Original corner was found by John Randall, County Surveyor, about 1884; Randall's record of distance betw Sec 18 & 19 is 80.12 chs. (dist found in present survey 80.03 chs.) The point for cor. is harmoniously related to the original cor. for sec 7, 8, 17, and 18. Set concrete monument 24" long, 6" in diam. 18" in the ground with 3 1/2" brass tablet embedded in top. 5" Poplar N54°45'E 64 lks (42.24') marked "T26N R1E S 17 BT"
5" Poplar S49°45'E 59 lks (38.94') marked "T26N R1E S 20 BT"
6" Poplar S55°30'W 26 lks (17.16') marked "T26N R1E S 19 BT"
20" Norway Pine N08°45'W 66 lks (43.56') marked "T26N R1E S 18 BT"

Wit:

1985 USFS Haase, Forest Technician

Mon - USGLO monument found

Wit: Found. 20" Norway Pine stump N08°45'W 43.56

6" W Pine N29°E 52.25

4" W Pine S30°E 11.31

3" W Pine (Twin) S61°W 10.87

Cedar Post S08W (Dist not given)