


**SURVEY &
REMONUMENTATION**

AUG 1 0 2005



RECORDED
LAKE COUNTY, MI
18 OCT 2004 2:34:21 PM

SHELLY MYERS
REGISTER OF DEEDS

Liber 5 Page 322

**SECTION
LAND CORNER RECORDATION CERTIFICATE**
Filling Requirement of Act 74, Mich., P.A. 1970

For corners in _____ Located in: _____ Corner Code# _____
Lake _____
(County)

1. Public Land Survey
T18N R14W _____
T_N_R_W _____ G-7
T_N_R_W _____
T_N_R_W _____
T_N_R_W _____
2. Property Controlling
in Section _____
S _____
3. Miscellaneous
Property in Sec. _____
S _____
T_N_R_W _____
T_N_R_W _____

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, **Robert L. Wetherell**, in a field survey on August 3, 2004, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

G-7 Section Corner 15-16-21-22

A. Description of original monument and accessories and/or subsequent restoration:

- 1838 Sibley, G.L.O.**
#1. 12" Hemlock S64°W 12 Lks.
#2. 24" Hemlock N76°E 34 Lks.

- 1908 G. West**
"Located by Hollister in 1904"
#3. 30" W. Pine stump N54°W 51 ½ Lks.
#4. 30" W. Pine stump S21°E 21 ½ Lks.

- 1926 G. Johnson, County Surveyor**
1" Iron pipe
#5. 14" B. Oak NW 170.5'
#6. 28" Pine stub SE 132'
"Check old witnesses (2 pine stumps o.k.)
Found old stake"

- 1937 Wm. Downey, M.S.H.D.**
1" Angle iron
#7. 6" Oak N25°W 48.90'
#8. Fence post S75°W 34.50'

- 1964 R. Griffin, L.S. 13584**
L.C.R.C. L.01, Pg. 114
"Found 5" cedar post set to replace the iron pipe (Johnson) and the 1" angle iron (M.S.H.D.)" Found remains of accessories #3, #4 and #7. Set 5" concrete monument
#9. 4" W. Oak N24°E 123.98'
#10. 7" B. Oak S68°E 95.27'
#11. 3" R. Pine S23°E 122.99'
#12. 4" R. Pine N42°W 124.47'
#13. 4" Maple N58°W 88.18'
#14. Post North 2.3'

- 1988 S. Barnett, L.S. 16923**
Unrecorded survey
#15. Distance West to ¼ Corner = 2548.16'
#16. Distance South to ¼ Corner = 2667.84'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I found Griffin's 5" concrete monument 360 ft. (+/-) North of hwy. U.S. 10. It checks well with all the recovered witnesses.


Condition of Accessories: #1, Gone, #2, Gone, #3, Gone, #4, Gone, #5, Could not identify, #6, Could not identify, #7, Gone, #8, Gone, #9, Found in good condition, #10, Found in good condition, #11, Found in good condition, #12, Found in good condition, #13, Found in good condition, #14, Found in good condition, #15, Did not measure, #16, Did not measure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

I accepted Griffin's 5" Concrete monument as a substantial marker for the corner as a careful and faithful reestablishment of the position of the original corner.

- | | | | | |
|-------------|-------|---------|--------------------------|-----|
| 16" W. Oak | S77°E | 77.74' | (60 d. spike in SW side) | |
| 15" R. Pine | S22°E | 123.00' | (60 d. spike in E side) | #11 |
| 10" R. Pine | N42°W | 124.60' | (Dock spike in E side) | #12 |
| 17" Maple | N58°W | 88.08' | (60 d. spike in NE side) | #13 |

Signed by Robert L. Wetherell Date 10-18-04
Surveyor's Michigan License No. 24624



RATIFIED BY THE LAKE CO. PEER REVIEW
GROUP IN ACCORDANCE WITH P.A. 345
CHAIRMAN R.W. DATE: 10-12-04

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS
REVISED JAN. 1993
ADAPTED FOR WORD PROCESSING JANUARY, 1999

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
1	2	3	4	5	6	7	8	9	10	11	12	13
14	15	16	17	18	19	20	21	22	23	24	25	26
27	28	29	30	31	32	33	34	35	36			