

SURVEY & REMONUMENTATION

SEP 11 2007

SECTION

Part A continued:

1912 Oscoda County Surveyor C.O. Seeley
1914 Mon.- Int'd 1.22 chs North of post 9-10-3-4(Established
by Power Co Survey of River) OK
South from post corner of Sec 3-4-9-10
Sec corner of 9-10-3-4
Wit: None given

1924 G.F. DeLaMater RLS #693
Mon.- Not given

Wit: S Pine 12" N23°W 38 ½ lks (25.41)
S Pine 12" N81°E 49 ½ lks (32.67)

1937 GLO Dependent Resurvey Guy R. Veal Cadastral Eng.
Mon.- Proportionate distance; there is no remaining
evidence of the original post or bearing trees.
Set a block of concrete, 8 ins. long, 6 ins. diam., 24 ins.
in the ground, in winding road which bears N. and S., for
deposit to mark cor.,

Wit: At a point S. 89° 33' W., 50 lks. (33.00) dist., from
the cor.,
Set a concrete monument, 24 ins. long, 6 ins. diam.,
18 ins. in the ground, for witness cor. of secs. 3, 4,
9, and 10, with brass tablet, 3 ½ ins. diam., 3 in.
stem, embedded in top and mkd.

Wits to Witness Corner:

A Jack Pine, 6 ins. diam., bears N. 22 ½° E., 99 lks.

(65.34) dist., mkd. W C T 26 N R 1 E S 3 B T

A Black Oak, 6 ins. diam., bears S. 62 ¼° E., 221 lks.

(145.86) dist., mkd W C T 26 N R 1 E S 10 B T

A Jack Pine, 6 ins. diam., bears S. 16° W., 183 lks.

(120.78) dist., mkd. W C T 26 N R 1 E S 9 B T

A Jack Pine, 8 ins. diam., bears N. 66 ¼° W., 205 lks.

(135.30) dist., mkd. W C T 26 N R 1 E S 4 B T

1978 survey Edwin J. McCombs RLS #10696
L3 P435 Mon.- Set Re-rod

& LCRC

L1 P233 Wit: 10" Jack Pine S85°E 31.75
15" Oak N20°W 34.77

8" Jack Pine S25°W 14.67

Set ½" rebar on West edge of trail 33 East of
found USGLO witness monument.

1980 survey Edwin J. McCombs RLS #10696
L3 P424 Mon.- Set Rebar on W edge of trail 33 E of
found GLO witness Mon
Wit: 10" Jack pine S85°E 31.75
15" oak N20°W 30.77
8" Jack pine S25°W 14.67

1987 survey Sammy S. Barnett RLS #16923
L4 P199-204 Mon.- Found 6" concrete monument w/brass cap.
& LCRC L3
P22

Wit: Placed a 60d spike in the side of, blazed and
scribed the face of and painted the following
Oak 8" S76°E 48.50
Oak 9" N05°W 24.75
Oak 7" S14°E 23.05
Carsonite post

2002 survey Sammy S. Barnett PS #16923
L202 P7879 Mon.- ½" rerod w/cap #10696
-7880 Wit: S47°E 8" B Oak 18.78

S19°W 9" J Pine 14.78

S48°W 8" B Oak 36.89

N26°W 14" B Oak 35.03

West USGLO Mon (WC) 33.00

Wits to Witness Corner:

S76°E 8" B Oak 48.50

S14°E 8" Oak 23.05

East ½" rerod w/cap #10696 33.00

2002 LCRC Carol A. Waite PS #43074

L5 P286 Mon.- Found ½" rerod with cap #10696 1 West of

the West edge of a N-S trail road and 33 East of the

GLO witness corner monument.

Wit: S47°E Fd 60d Nail in E Face 8" B Oak 18.78

S19°W Set 60d Nail in SE Face 9" J Pine 14.78

S48°W Fd 60d Nail in N Face 8" B Oak 36.89

N26°W Set 60d Nail in W Face 14" B Oak 35.03

West GLO concrete monument w/brass cap 33.00

Wits to Witness Corner:

S76°E Fd 60d Nail in E Face 8" B Oak 48.50

S14°E Fd 60d Nail in N Face 8" B Oak 23.05

East ½" rerod with cap #10696 33.00