

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>33</u> ^{N.} X. , R. <u>3</u> ^{K.} W.		<u>I-3, J-3 & J-5</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, R. _____, ^{N.} S. , ^{E.} W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, R. _____, ^{N.} S. , ^{E.} W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

State of Michigan
 County of Cheboygan
 Received for Record
 SEP 20 1977 At 3:43 PM AM

Jean Simoneau
 Register of Deeds

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Orlando Doyle, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

I-3 Set 1/2" Pipe			
8" Maple	N. 50 deg. E.		32.35
10" Beech	S. 15 deg. W.		41.16
5" Maple	N. 20 deg. W.		36.71
J-3 Found 3/4" Pipe			
Power Pole	N. 45 deg. W.		30.85
Power Pole	N. 64 deg. E.		36.95
4" W. Pine	S. 36 deg. E.		82.35

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-5 Found 3/4" Rod in centerline of Road			
15" Maple	N.N.W.		48.15
12" Maple in clump	W.N.W.		38.89
9" N/ Pine	S. W.		54.22

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:



SIGNED BY *Orlando Doyle* DATE Sept. 21, 1977
 SURVEYOR'S MICHIGAN REGISTRATION NO. 7319 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

LIBER 001 PAGE 224

SURVEYOR'S MICHIGAN REGISTRATION NO. _____