

Walmart

8

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. 33 <sup>(N)</sup> S., R. 3 <sup>(E)</sup> W.		J2, I2, H2
2. PROPERTY CONTROLLING IN SECTION <u>2,3</u> , T. 33 <sup>(N)</sup> S., R. 3 <sup>(E)</sup> W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____ , T. _____ S., R. _____ E. W.		
4. LOT NO. _____ , RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

RECEIVED FOR RECORD  
 93 MAR -4 PM 12:31  
*James Gray*  
 CLERK/REGISTER  
 CHEBOYGAN COUNTY, MICHIGAN  
 REGISTER OF DEEDS STAMP AND FILING NUMBER

I, \_\_\_\_\_ do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on July 1992, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  
 J2 - Found 1/2" Rod @ centerline of Wolverine Road (20' Paved) at centerline of intersecting Peters Road (18' Gravel). Set Monument Box.  
 I2 - Found 1/2" Rod @ centerline of Wolverine Road (20' Paved) at centerline of Collins Road. Set Monument Box.  
 H2 - Found 1/2" Rod @ centerline of Wolverine Road in line with fence line. Set Monument Box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
 J2 - 1/2" Rod, Center cor. Sec. 2  
       6" Ash, S 50° E, 78.65'  
       8" Ash, S 45° W, 74.70'  
       Fence Post N. 10° W. 72.99'  
       Fence Post N. 40° 30' E. 78.97'  
 H2 - Center corner, Sec. 3, 1/2" Rod  
       6" Ash N 73° E 79.58'  
       12" Red Pine S 11° E 51.33'  
       P.P. S 44° W 43.44'  
       P.P. N 45° W 55.22'

ORDER 002 PAGE 201



SIGNED BY Mark A. Emnes DATE 1-8-93

SURVEYOR'S MICHIGAN REGISTRATION NO. 25842

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_