

SURVEY & REMONUMENTATION

JAN 24 2006

Alcona County Remonumentation Liber 3 Page 113

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ALCONA

(County)

2005 Alcona County Remonumentation Located In: Corner Code #

T25N, R8E

1. Public Land Survey

T R E-10

2. Property Controlling in Section

S

3. Miscellaneous Property in Sec.

S

4. Lot No. , Recorded Plat

5. Private Claims

I, John F. Oliver, in a field survey on Dec. 10 2005 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-10: 1843: GLO sur. by J. Mullett - set post and referenced 1998: sur. by J. Oliver - set 1/2" rod and cap midway and on line between E-9 and E-11 referenced:

- 6"-2"-2" maple - S 65°E - 72.50'
12"-2"-4" maple - S 35°E - 77.60'
p. pole - N 78°W - 24.40'
4" ash - S 20°W - 51.82'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-10: fd. 1/2" rod (no cap) 9 feet West of centerline of N-S rd with a fence line running West from the corner no evidence recovered from GLO survey of 1843 four previous witnesses from 1998 survey recovered accepted

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


E-10: placed stamped alum. cap on the 1/2" rod referenced:
6"-2"-2" maple - S 63°E - 72.50'
12"-2"-4" maple - S 38°E - 77.81'
p. pole - N 77°W - 24.54'
5" ash - S 18°W - 51.83'

Handwritten signature of John F. Oliver

Signed by John F. Oliver

Surveyor's Michigan License No. 19840

Date Dec. 14, 2005



APPROVED LAND CORNER P.A. 645 of 1990 ALCONA COUNTY Date 12-20-05 County Rep [Signature]

Grid table with columns A-M and rows 1-13. A dot is present at row 10, column J.

Register of Deeds Stamp & File Number

Alcona County Remonumentation Liber Page

Filed for Record in ALCONA COUNTY MICHIGAN KAREN V HEALY 01-03-2006 At 09:26 am. LAND CORNER 14.00

received 12-24-2005