

**SURVEY & REMONUMENTATION**

JAN 24 2006

**SECTION**

Alcona County Remonumentation  
 Liber 3 Page 112

**LAND CORNER RECORDATION CERTIFICATE**  
 Filing Requirement of Act 74, Mich. P.A. 1970

2005 Alcona County Remonumentation

Located In: Alcona County Corner Code # E-11

(County)

- 1. Public Land Survey \_\_\_\_\_
- 2. Property Controlling in Section \_\_\_\_\_
- 3. Miscellaneous Property in Sec. \_\_\_\_\_

0  
 Filed for Record in  
 ALCONA COUNTY MICHIGAN  
 KAREN V HEALY  
 01-03-2006 At 09:26 am.  
 LAND CORNER 14.00

Received 12-29-2005

Alcona County Remonumentation  
 Liber \_\_\_\_\_ Page \_\_\_\_\_

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
 5. Private Claims \_\_\_\_\_

T25N, R8E

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, John F. Oliver, in a field survey on Dec. 10, 19 2005 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

E-11: 1843: GLO sur. by J. Mullett-set post and referenced  
 1998: sur. by J. Oliver - fd. 1" pinch top pipe  
 date unknown: sur. by NE sur. - cor. not identified

APPROVED LAND CORNER  
 P A 345 of 1990  
 ALCONA COUNTY -

Date 12-20-01  
 County Rep. J.F.O.

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

E-11: fd. 1/2" rod with no cap 1 foot West of N-S rd centerline with a fence line running West from the corner


no evidence recovered from GLO survey of 1843

distances and alignment are compatible with previous surveys accepted as the correct location for the corner

**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

E-11: placed stamped alum: cap on the 1/2" rod referenced:

- p.pole - West - 36.02'
- 10 tw. maple - S 40°E - 48.04'
- 8" balsam - N 73°E - 30.28'
- 6" cherry - S 35°W - 76.60'



Signed by John F. Oliver Date Dec. 14, 2005  
 Surveyor's Michigan License No. 19840

