

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in ALPENA (County)

Located In: Corner Code =#

- 1. Public Land Survey T 31N R 5E
2. Property Controlling in Section S 5 T R 1,2,3,4
3. Miscellaneous Property in Sec. S T R
4. Lot No. Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Grid table with columns A-M and rows 1-13. Contains numerical data and corner markers.

I, CARL KIISKILA, in a field survey on NOVEMBER 1, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1 (NO EVIDENCE OF G.L.O. CORNER, BT'S, LINE TREES & TOPOGRAPHY, AS CALLED OUT IN THE G.L.O LINE NOTES; UNLESS NOTED IN ITEM "B" BELOW.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1 ESTABLISHED THE NW CORNER OF THE FRACTIONAL NE 1/4 OF THE FRACTIONAL NW 1/4 SEC 5 BY STANDARD PROCEDURE FOR SUBDIVISION OF A SECTION.
2 ESTABLISHED THE NW CORNER OF THE FRACTIONAL NE 1/4 OF THE FRACTIONAL NE 1/4 SEC 5 BY STANDARD PROCEDURE FOR SUBDIVISION OF A SECTION.
3 ESTABLISHED THE NW CORNER OF THE SW 1/4 OF THE FRACTIONAL NW 1/4 SEC 5 BY STANDARD PROCEDURE FOR SUBDIVISION OF A SECTION.
4 ESTABLISHED THE NE CORNER OF THE SW 1/4 OF THE NW 1/4 SEC 5 BY STANDARD PROCEDURE FOR SUBDIVISION OF A SECTION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Table with 4 columns of monument descriptions and measurements, including items like 'DROVE 5/8" x 32" REROD W/PS CAP', 'POWER POLE', 'CEDAR POST', '6" TAMARACK', '4" SPRUCE', '10" POPLAR', '8" MAPLE CLUMP', '6" SPRUCE', '3" SPRUCE', 'CEDAR POST SOUTH', '10" SPRUCE', 'FENCE COR', '2" SPRUCE', '4" SPRUCE', '14" SPRUCE', '8" SPRUCE', '6" TRIMAPLE', 'CEDAR POST'.

Signed by Carl T. Kiiskila 33981
Surveyor's Michigan License No.

Date

1-25-95

