

The purpose of this meeting was to locate or establish the land corner necessary for the proper identification of the state lands in this township.

The county record contains very little information concerning previous surveys in the SW 1/4 of this township. Several corners in the SW 1/4 of this township were located, and shown on the county record. The corners were generally established by the Government Land Office and were generally marked by iron pipes. The following is a description of the corners found and noted:

1. Corner to sections 18 and 19 on west boundary. Found a 1 1/2" iron bar, about 11" west of center of road, which is presumed to project to the corner as established in a road survey by L. Campbell, Sr. in 1901.
2. Corner to sections 17, 18, 29, and 30. Found a 1 1/2" pipe in center of road, in line with fence west and west, possibly by Campbell.
3. Corner to sections 16, 17, 20, and 21. Found 3" iron pipe in place of record by L. J. Finner in 1898 as set from original S. 1.
4. Corner to sections 15, 16, 20, and 21. Found a 1 1/2" concrete marker, which center the center of the road east as recorded by Finner in a survey made in 1910. A 2 1/2" concrete marker east appears to be tied to this corner.
5. Corner to sections 17, 20, 31, and 32. Found a 1 1/2" concrete marker and very old post, recorded by Finner in 1910. The post was found west of road centerline and close to the corner.
6. Corner to 31 and 32 on north boundary. Found a 3/4" iron pipe in center of road, in line with fence west of centerline of road, as recorded by Finner in 1910. A 2 1/2" concrete marker west and an old fence post close to the corner.

The west boundary presented a problem, since no corner could be found west of the corner to 31-32. The corner to 31-32 was found to be a 2 1/2" concrete marker, which was found to be in line with the center of the road. The corner to 31-32 was found to be a 2 1/2" concrete marker, which was found to be in line with the center of the road. The corner to 31-32 was found to be a 2 1/2" concrete marker, which was found to be in line with the center of the road.

A description of the SW 1/4 of this township, as indicated on the map, was the result of a survey made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901.

The interior corners of the SW 1/4 of this township, as indicated on the map, were the result of a survey made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901.

The center of the SW 1/4 of this township, as indicated on the map, was the result of a survey made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901. The survey was made by the Government Land Office in 1901.

All bearings shown on the attached map are related by transit angles to a solar observation on the west line of Section 15. The corners were established by divided from the record.

MAP OF PART OF
 T25NR9E
 ALCONA CO MICH
 FOR
 FORESTRY DIVISION
 DEPT. OF CONSERVATION
 1958

