

MAR 03 2000

LAND CORNER RECORDATION CERTIFICATE

SECTION FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Alcona County Remonumentation 1999

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T.25N N. S., R.5E E. W.	E-8
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. S., R. _____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. S., R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

Alcona County
Remonumentation
Book 2 Page 24

0
Filed for Record in
ALCONA COUNTY MICHIGAN
DORIS A GAUTHIER
On 12-17-1999 At 10:32 a
LAND CORNER 9.00

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, John F. Oliver do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on Dec. 8 1999, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- E-8: 1845: GLO survey by J. Mullett - set post and referenced
 1914: sur. by A. Freer - cor. is slay shoe 34" long-3" wide with crockery
 1931: dependent resur. by G. Veal - set brass tablet on 6" x 24" conc. mon.
 1975: sur. by N. Caldwell - no description of corner

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-8: found 6" x 24" conc. mon. with brass tablet
 no evidence recovered from GLO survey of 1845
 distances and alignment are compatable with Veal and Caldwell surveys
 one previous witness found
 accepted as the correct location for the corner

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- E-8: 6" x 24" conc. mon. with brass tablet
 referenced:
 (from 1931 survey) 23" r. pine / N 57°E / 128.51' to nail
 5" oak / N 65°E / 55.03' to nail
 11" oak / S 75°W / 67.20' to nail
 5" w. pine / S 32°E / 36.55' to nail

APPROVED LAND CORNER
 P A 345 of 1990
 ALCONA COUNTY
 Date 11/30/99
 County Rep. [Signature]

SIGNED BY [Signature] DATE Dec. 8, 1999
John F. Oliver
 SURVEYOR'S MICHIGAN REGISTRATION NO. 19840

FOR STATE AND UNITED STATES AGENCIES:
 SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

