

**ALLEGAN CO. REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

<u>ALLEGAN</u> (County)	Located In:	Corner Code ≠
1. Public Land Survey	T- <u>1N</u> R- <u>12W</u>	<u>A-11, NW 31</u> <u>OTSEGO</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____

97 JUN 22 PM 1:27
REGISTERED
ALLEGAN COUNTY
REGISTER OF DEEDS STAMP & FILE NUMBER
FILED

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, BASIL ADDRESS, in a field survey on JUNE 8, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules theretofore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	16	17	18	19	20	21	22	23	24			
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O.

78.67 TO W. BOUNDARY 9 LKS S OF COR
SET POST COR SECS 30 & 31
BEECH 8 S 74° E 17
BEECH 10 N 43° E 31

1979 D.A. RATEKIN, C.S.
WITNESS CARD
Fd 3/4" PIPE IRON N 5.94'
CUT NAIL NW SDE PP
N 50° E 42.92
C.L. 102ND AVE N 2'±
E. END 15" RCP S 45° E 35.76'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Fd 3/4" IRON IN MON BOX ON LINE BETWEEN M-11 & M-12 TROWBRIDGE
M-11 TROWBRIDGE N 5.94'
E. END 12" R.C.P. S 45° E 35.4'
P.P. N 50° E 43.5'
C.L. 102ND AVE N 2'±
AND IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF
THE ORIGINAL CORNER.
REPLACED 3/4" IRON W/ STD ALLEGAN CO. MON. IN MON. BOX.

APPROVED REMONUMENTATION CORNER
P.A. 343 OF 1990
ALLEGAN COUNTY
DATE APPROVED 5-14-96
COUNTY REP. [Signature]

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

ALLEGAN CO. MONUMENT
16d & ALLEGAN CO. TAG NW SDE P.P. N 50° E 43.50
CEN. TOP TEL PED S 45° W 50.97'
CEN. E. END 12" CONC. PIPE S 45° E 35.43'
16d & ALLEGAN CO. TAG E. SDE 4" MAPLE S 15° W 82.05'
W. EDGE W. SIGN POST N 10° E 22.87'
M-11 TROWBRIDGE TWP. (STD. ALLEGAN CO. MON) N 5.94'
C.L. 102ND AVE N 2'±
IN LINE W/ C.L. 24TH ST TO SOUTH



Signed by [Signature] Date 10 JUN 96
Surveyor's Michigan License No. 30075

REF: 0005 PAGE 485