

MAR 07 2000

FILED

ALLEGAN COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
FILING REQUIREMENT OF ACT 74, MICH. P. A. 1970

SECTION

00 FEB -1 11 8:36

11000007 PAGE 1 77

FOR CORNERS IN: ALLEGAN COUNTY	LOCATED IN:	CORNER CODE #
1. Public Land Survey	T.1N... R.14W...	M-11
SOUTHEAST CORNER OF SECTION 25, T1N, R14W, NORTHEAST CORNER SECTION 36, T1N, R14W.	T..... R.....	CHESHIRE TWP.
	T..... R.....	
	T..... R.....	
2. Property Controlling in section	S.....T.....R.....	
	S.....T.....R.....	
3. Miscellaneous Property in Sec.	S.....T.....R.....	
4. Lot No.....Recorded Plat.....		
5. Private Claims.....		

REGISTER OF DEEDS STAMP & FILE NUMBER

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	16	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Raymond Moored in a field survey on AUG. 5, 1999 do hereby state that under requirements of P.A 74, Michigan P.A of 1970, corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in the lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, monumented, recovered, found as expressed below.

Note: Not more than 2 corners, all the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

SEE BACK OF SHEET FOR CORNER HISTORY

APPROVED REMONUMENTATION CORNER  
P.A. 345 OF 1990  
ALLEGAN COUNTY  
DATE APPROVED DEC. 14, 1999  
COUNTY REP. *[Signature]*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:  
FOUND 1/2 IRON WITH CAP PER ITEMS NUMBER 3 & 4 LISTED ON BACK OF SHEET.

SET 3/4" X 24" ALLEGAN COUNTY REMON IRON WITH CAP IN PLACE OF FOUND CORNER.  
ACCEPTED POSITION AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

APPROVED BY ALLEGAN COUNTY REMONUMENTATION PEER GROUP ON DEC. 14, 1999.

TOTAL ON ROAD TRAVERSING= 2642.22'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET STANDARD 3/4" X 24" ALLEGAN COUNTY REMONUMENTATION IRON WITH CAP.  
FACE of 14" WALNUT S 15° E 31.50  
NAIL & TAG IN 12" ASH S 5° E 32.82'  
NAIL & TAG IN P. POLE S 20° W 58.70'  
C/L PAVED ROAD NORTH 34.60'  
A-11, T1N, R13W N 60.98'

*[Signature: Raymond Moored]*  
Date: 12/24/99

Surveyors License No. 26463



SURVEY &  
REF

MAR 07 2000

SECTION

**GOVERNMENT CORNER HISTORY FOR  
CHESHIRE TOWNSHIP, ALLEGAN COUNTY, MICHIGAN  
M-11  
TOWN 1 NORTH, RANGE 14 WEST,**

- 1. GLO  
80.00 TO W. OAK 30". COR TREE TO SECTION 25 & 36
- 2. COUNTY SURVEYOR NOTES, CIRCA 1900'S  
M-11 WEST TO L-11 = 2607
- 3. D.A. RATEKIN, CO. SURVEYOR; SECTION CARD INFORMATION, 1982  
1/2 " IRON W/CAP  
FACE OF 14" WALNUT                    S 15° E 31.5'  
FACE OF 12" ASH                        S 5° E 32.8'  
S. EDGE OF POST ( ZONING SIGN)    N 70° E 29.35'  
C/L ROAD                                 N 34.6'  
SW CORNER OF SECTION 30            N 60.98'  
( TROWBRIDGE TOWNSHIP)
- 4. MOORED LAND SURVEYING, 9-17-97  
SURVEY NOTES 1" IRON W/CAP  
M-11 SOUTH TO M-12 = S 1°04'45"W 2644.87  
L-11 EAST TO M-11=    N 89°45'16"E 2604.12

