LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CURNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	
1. PP M.IC LAND SURVEY	т. 1 / к. 14	C-2, C-3, C-1	HE K
2. PROPERTY CONTROLL- ING IN SECTION	N,	la	1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
S, MISCELLANEOUS PROPERTY IN SECTION			FILED PH 19 ALEGISTER OF DEEDS ALEGISTER OF DEEDS
4, LOT NO	ORDED PLAT		8033 9033 1161 H.
5, PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
field survey on NOVEMBER restored as expressed below a of survey instructions of the U court of law. Furthermore, 19	n lines I and 2 above 1	(identified with circles on ind lished, re-established, monume a regulations and rules therefore at of the Interior, Bureau of Lan ats mentioned in lines 3,4 and ared, established or re-established	of P.A. 74, Michigan P.A. of 1970, ex code diagram—over) were, in a need, re-monumented, recovered or eas required in the current manual and Management or by a decree of a 15 above were, in a field survey on ed as expressed below and in conyors or, by a Decree of a Court of
<u>C-2</u>		<u>c-3</u>	<u>C-1</u>
B. Description of corner eviden C=2 Set 1 th I non	nce found and/or metho	od applied in restoring or re-est C-3 Fo. 1%" From	ablishing corner: C-1 Fo. 5/8" Inon
	or corner and accessor	ies established to perpetuate le	ocating the position of the corner:
<u>C-2</u> 1" ROM		C-3 1X" IRON	C-1 5/8" (non
1" INON S60°-33'-13'W (THAVERSE POINT) NATE IN 6" BASS CLUST NATE IN 3" OAK S45°W		NW COR TEL. BUTLET N35°E 39.46' Nate in 30" Abn	15" ASH S60°W 81.15' 20" MAPLE S50°E 64.8' 15" SYCAMORE N 61.6' 10" ASH \$50°W 86.6'
SIGNED BY TOUNG DOMALD A. RATEKIN & ABB SURVEYOR'S MICHIGAN REG	•	781 DATE	1-22-74 MICHIGANA STATE OF MICHIGANA
FOR STATE AND UNITED STA	ATES AGENCIES:		DONALD X.
SIGNED BY	EMIEF OF BURYEY PARTY	DATE	LAND SURVEYOR
APPROVED AND SIGNED BY		THE CAMB BURNEYOR DATE	3 % No. 8781 155 E
			WASTAND THE
SURVEYOR'S MICHIGAN REGI	STRATION NO.	FORM APPROVED BY MICHIGAN STATE	SOARD OF REGISTRATION, JAM. 26, 1971