11121111

ALLEGAN COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

22

27

34

23

26

35

21

28

33

20

29

24

25

36

For corners in					FILED	
Allegan (County)		Located	In:	Corner Code #	1/28/1999 2:44:39	PH
1. Public Land Survey		T2N T T	R15W R R	I-13 Clyde Twp.	JOYCE A. WATTS RESISTER OF DEEDS ALLEGAN COUNTY: MI	
 Property Controlling in Section Miscellaneous Property in Sec. 	s s s	T T T	R R R R		Register of Deeds Stamp & File Number	
4. Lot No, 5. Private Claims	Record	ded Plat			A B C D E F G H I J K	L N
do hereby certify that under in lines 1 and 2 above we	require	ements of P.A. onformance w	. 74, Michigan ith regulation	ber 1, 19 98 . P.A. of 1970, the corner points me is and rules therefore as required partment of the Interior, Bureau of	ntioned 5	12

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a

Court of Law; established, re-established, monumented, re-monumented, recovered, found as

Description of original monument and accessories and/or subsequent restoration:
1905 County Surveyor Records

Calvin Britain

expressed below:

J-13 East, Town 2 North, Range 15 West 2643.25'

Set post Pine 30 N 67 E 20 Pine 8 N 55 W 19

1984 County Surveyors Records Set 1/2" pipe with cap Nail S side 13" W Cherry S 60 W 29.00' NE side 12" W Cherry S 15 E 42.00' Centerline 112th Ave. (gravel) S 10'± Centerline 52nd St. (gravel) W 6'±

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" pipe with cap #26463 Nail E. side 13" W. Cherry S 60 W 29.10' Nail E. side 12" W. Cherry S 15 E 42.10'

Centerline 112th Avenue (gravel) extended South 10 $^{\circ}\pm$

Centerline 52nd Street (gravel) extended West 6'± pulled 1/2" pipe with cap and set standard Allegan County Remonumentation 3/4"x36" iron with red cap #23520. Approved by Allegan County Remonumentation Peer Group November 10, 1998 and is accepted as a careful and Faithful perpetuation of the position of the original corner.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990 ALLEGAN COUNTY

DATE APPROVED NOUS

19

30

7

8

10

11

12 31

13

Э.	Desc	ription o	of monum	ent for co	rner and	nd accessories established to perpetuate locating the position of the cor	mer:
stand	lard	Allegan	County :	Remonumen	tation	n 3/4"x24" iron with red cap #23520	
[-1,	T1N,	R15W,	Standard	Allegan	County	y Remonumentation 3/4"x24" iron with red cap #23520 East 62.04	1
ail	with	Alleca	n County	Remonume	ntation	on tag W side 8" Charme 6 15 W 40 071	

Nail with Allegan County Remonumentation tag E side 12" Cherry S 19 E 41.90"

Top center telephone cable box S 49 E 53.14

N steel traffic sign post S 63 E 2.93'

		1 10	011
Cianad	hu Aca	- <i>UMI</i> -	Petolo
Signed	DY VY	18800	1000

Surveyor's Michigan License No. 25867

Date DRUMBER 29

OF MICH DONALD R PITTS, JR LAND SURVEYOR NO. 25867 ESSION

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SUR FATE BOARD OF LAND SURVEYORS, JAN. 28, 1977 REVISED MAY 14, 1975 REVISED JAN., 1983 ADAPTED FOR WORD PROCESSING MARCH, 1993