

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF-:	LOCATED IN-:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 2 N. R. 15 W.	G-2 G-3
2. PROPERTY CONTROLLING IN SECTION	T. N. R. E.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E.	
4. LOT NO. _____	RECORDED PLAT _____	
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS
MICHIGAN
MAY 4 11 13 AM 1972
FILED
REGISTER OF DEEDS STAMP AND FILING NUMBER

I, DONALD A. RATEKIN do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on OCTOBER 28, 1971, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

<u>G-2</u> GOV'T NOTES - W. OAK 16 S 85 E 51 Do 12 N 75 W 24	<u>G-3</u> GLO PINE 14 N84E 22 W. Ash 14 S43W 39
---	---

sw 3

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<u>G-2</u> FOUND 1/2" REF. ROD	<u>G-3</u> FOUND SOLID BAR.
-----------------------------------	--------------------------------

sw 3

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>G-2</u> FOUND 1/4" REF. ROD ST. SIGN W 20.7' NAIL IN S. ROOT 16" OAK 55°E 44.39' 9" PINE 58°W 36.7'	<u>G-3</u> SOLID BAR. PK NAIL SE ROOT 18" PINE N45°W 67.57' PK NAIL P. POLE S40°W 66.80' ST. SIGN S45°E 34.85'
--	--

SIGNED BY Donald A. Ratekin DATE 4-18-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 8781

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. _____
FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS