

**LAND CORNER RECORDATION CERTIFICATE**  
**FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970**

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
2. PROPERTY CONTROLLING IN SECTION <u>35</u> T. <u>3</u> N. _____ E. _____ R. <u>15</u> W. _____		<u>12 8</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____ T. _____ N. _____ E. _____ S. _____ R. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

JAN 13 8:42 AM 1970  
*John A. Stearns*  
 FILED

I, DONALD A. RATEKIN do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram-over) were, in a field survey on APRIL 28, 1976, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:  
12 8

*w/6 cor SW 1/4 35*

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:  
12 8  
 SET  $\frac{1}{2}$ " PIPE (18" LONG) WITH CAP MIDWAY BETWEEN S 1/4-POST AND CENTER SEC-35  
 SET  $\frac{1}{2}$ " PIPE WITH CAP MIDWAY BETWEEN W 1/4-POST AND CENTER SEC-35.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:  
12  
 $\frac{1}{2}$ " PIPE WITH CAP  
 PK NAIL 16" OAK E 4.92'  
 PK NAIL 6" W. OAK N40°W 10.0'  
 PK NAIL 9" W. OAK S40°W 5.37'

8  
 $\frac{1}{2}$ " PIPE WITH CAP  
 PK NAIL N SIDE OF N. OAK 10"-14"-16"  
 S45°W 31.55'  
 PK NAIL S SIDE 6" CHERRY N70°E 67.42'  
 PK NAIL E SIDE 12" OAK N45°W 57.14'  
 BLAZE MARKS IN ALL TREES


SIGNED BY Donald A. Ratekin DATE 12-28-76

SURVEYOR'S MICHIGAN REGISTRATION NO. 8781

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_