## ALLEGAN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For comers in	_	·	ı.		^		
ALLEGAN (County)	Located In:	Corner Code #			Ezok	97	
1. Public Land Survey SEC. COR. COMMON TO	TR	C-13 MANLI	US: TWF.		القطاطية القطاطية القطاطية	JAH 22	=
SEC. 31 & 32 T3N, R15W  2. Property Controlling	TR S TR					<b>≅</b> <del></del>	T D
in Section 3. Miscellaneous Property in Sec.	S TR S TR S TR			Б	• •	26	
•			<u> </u>	Register	of Deeds S	tamp & Fi	le Number
5. Private Claims	orded Plat		1	A B C	D E F	G H I	J K L I
			2 3	'i i i	- 5	┼┋┼	-21
conformance with regulations as	gan P.A. of 1970, the corner p nd rules therefore as required in	OCT 19 % do hereby a points mentioned in lines 1 and 2 to the current manual of survey insagement or by a decree of a Court	state that under 4 above were in tructions of the 5	<del> </del>  -	9-	10	-1112
that the corner points mentions	ed in lines 3, 4 and 5 above wer by a Decree of a Court of Li	re in conformance with the rules of aw, established, re-established,	f the Michiczn		70 71	15	1 1
NOTE: Not more than 2 co	mers, all in the same town a	nd range, may be recorded	9		Ĭ		
on this certificate.			10		29 28	27	26-25-
			12		32-33-	34	35-36-
A. Description of original m	onument and accessories	and/or subsequent restoratio	. 13 n:	,l <b></b>	<u> </u>	<u> </u>	نطلك
S	EEE SHEET 2 OF 2 FOR C	Corner History	DA	A ATE APPRO	EMONUMENT P.A. 345 OF I LIEGAN COL LIEGAN COL	990 אדאר ַ	
B. Description of corner ev	idence found and/or metho	od applied in restoring or rees		OUNTY REF	*- <sub>-</sub>		
FOUND 1/2" IRON IN MOI 277.70"; RATEKIN MEASU CAREFUL & FAITHFUL P. COUNTY REMON IRON A FRAVERSED 5270.6" ON R	RED 278", MEASURED F ERPETUATION OF THE IND CAP. APPROVED F	EAST TO D-1, T.2N., R.15V ORIGINAL CORNER. SE	7. 2394.60°. ACC	EPTED P	OSITION A	¢	
NAIL & TAG IN E. NAIL & TAG IN W NAIL & TAG IN E. 2-1, T.2N., R.15W. W	LEGAN COUNTY REMO  V. SIDE TELE POLE S. SIDE 24" PINE V. SIDE 24" BLACK OAK	ONUMENTATION IRON V S45°E 34.98' N45°E 90.42'	cating the position		* PR	AYMOND MOORED OFESSION FURVEYOR NO. 26463	VAL MY 등
Signed by Our	Mored		Date 12/13	196	TITININ	FESSION P	Milling.
Surveyor's Michigan License	No 26463	<del></del>					

## GOVERNMENT CORNER HISTORY

## SEC. COR. COMM. TO SEC. 31 &32 TOWN 3 NORTH, RANGE 15 WEST

C-13

G.L.O (LYON)	-	80.00 SET POST SEC. 31 & 32 HEMLOCK 8 N41 1/2E 31 BIRCH 26 N45°W 33
CHICHESTER		COUNTY SURVEYOR NOTES AT S.W. COR SEC 32 LONGISH STONE IRREGULAR SHAPE, "X" ON TOP ALSO NORTH SIDE
MAC DOUGALL		1900'S BLACK WITNESS BOOK SET PIN ? APPLE 18" N.E. 94.6' PEAR 4" S. 49.2' APPLE 14" S.E. 65.4'
ALLEN	1962	SHOWS COR ON SURVEY, NO WIT, S.E. SEC 31
RATEKIN	1964	SHOWS COR ON SURVEY, NO WIT, S.E. SEC 31
RATEKIN	1971	SHOWS COR ON SURVEY  FIRE HYDRANT N30°E 65.4'  N.E. COR HOUSE SUUTH 78.8'  N.W. COR HOUSE 93.4'
RATEKIN	1971	L.C.R.C. LIBER 1, PAGE 131 WITS SAME AS 1971 RATEKIN SURVEY
RATEKIN · ·	1973	SHOWS COR ON SURVEY, NO WIT, S.E. SEC 31
MITCHELL	1991 ·	WITNESS CARD, WITNESSES ARE SAME AS 1971 RATEKIN SURVEY CLYDE COR WEST 278.00' SET 40d NAIL FROM WITNESSES, LIBER 1, PG 131
HOLLAND ENG.		WITNESS CARD  NAIL  FIRE HYDRANT  N.E. 65.40  N.E. COR HOUSE  S. 78.80  N.W. COR HOUSE  S.E. 93.40  LIBER 4, PAGE 383  STEEL BAR W/CAF  N.E. COR HOUSE  180°  78.80  N.W. COR HOUSE  180°  78.80  N.W. COR HOUSE  140°  93.40  C/L HYDRANT  30°  65.66  PK NAIL FACE P.P.  300°  74.39