## SURVE REMONUMENTALL

APR 2 9 1000

ALLEGAN COUNTY REMONUMENTATION

ALLI	7 P W IA	CO	014 1 1					
ANIO	COPA	1EB	RFC(	ORDA	ATIC	ON CE	ERTI	FICATE
MIND	CON	4 1 1 ×				B 81 - L	DA	4070

Filing Requirement of Act 74, Mich. P.A. 1970

FILED	00	
1/28/1999 2:44:39 PH	06	
JOYCE A. WATTS REGISTER OF DELDS ALLEGAN COUNTY, HICH	PAUL	

For corners in Allegan Corner Code # Located in: Leighton Twp. (County) T 4N R 11W 1. Public Land Survey 2. Property Controlling in Section 3. Miscellaneous Property in Sec.

Register of Deeds Stamp & File Number

\_, Recorded Plat 4. Lot No. 5. Private Claims

 $_{-}$ , 19  $\frac{98}{-}$  do hereby state that under 10-22 Robert J Jonker in a field survey on . requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate.

А	в с	DE	F G	н_1	JК	L M
1	ŤŤ	$\neg$	$\neg \neg \neg$	_1		
2	6-	╌┊╼┼	- <del>1</del> - †	-3-1		_ ; _
3	╂╌╂	╼╂╾╂			+-	
4		- 8-	9	10	-11-	-12-
5	+	┝╌┼╌┤	-+-			1
6	-18	17	16	15	14	13
7 -						
8	-1'9	20-	21	2'2	23	24 
9	<del> </del>	<b>  </b>		┝╼┾╾	┝╼┾╌	<del>                                     </del>
10	_30	29	28	27—	-26	25
- 1		<u> </u>			<del> </del>	
11			33	_34_	35_	36_
12	-31 I	<del>  -32</del>	1	Ī	lĩ	<u>l</u> _
	1	·				

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. post beech 18 S32W 27 5 N52W 20 Beech

(see additional info over)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found pk. nail on twp. line by wit. listed in "A" above cover)

And is accepted as a careful and faith ful perpetuation of the position of the original corner. APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990 ALLEGAN COUNTY DATE APPROVED NOV.

C. Description of manument for corner and accessories established to perpetuate locating the position of the corner

Replaced with std. Allegan Co. monument SW cor. brick house N55°E 126.41' Ameritech utility box #4592 S70°E 111.77'
Found pk in S. Side p. pole S50°W 54.31'
NE Cor. house fundation S70°W 111.35' Allegan Co. Remon pin North 9.18'

ROBERT J JONKER ROFESSIONA RVEYOR No. 21572 ROPESSEN

Q1572 Surveyor's Michigan License No

11-9-98

Sheet 1 of 2

A-3 LEIGHTON TWP.

1. Rec. survey by excel eng. 1973 L. 834, P. 252 calls for a spike in pavement 9.24' South of the Dorr Corner

10-22-98 check ok

2. Rec. survey by Ratekins, 1973, L. 839, P. 670? calls for a spike on C/L pavement 9.24' South of the Dorr Corner

check ok

3. 1973, Excel eng., LCRC #2-99
calls for a spike at the Leighton
corner which is 9.24' S. of the Dorr Corner

check ok

APR 2 9 1000

SECTION