For cornersSECTION Allegan.

1. Public Land Survey

J-1 (N $\frac{1}{2}$, 2)

Corner Code ##

Overisel Twp. R R R 2. Property Controlling in Section Miscellaneous s R Property in Sec.

Located in:

T 4N R 14W

Register of Deeds Stamp & File Number

... , Recorded Plat 5. Private Claims


John C. Bueche in a field survey on Мау to hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

J-1 GLO Not set

Tri-County, July, 1983 Nail in top of stump at intersection of fences as established by Co. Surveyor on survey dated April 21, 1967



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-1 Placed corner on South line of Twp. to the North midway between NW cor. & NE cor. Sec. 2, 2.78' West of S 1/4 35, 5-14; on field division E-W on West edge woods South

Meas. East 2621.46', NE 2

Traverse I-13 to J-13 2646.68' Meas. West 2621.46', NW 2 This position not established by original government surveyors. This monument is

accepted as the best available evidence of the position of the corner.

Peer group approved May 13, 1997.

APPROVED REMONUMENTATION CORNER

P.A. 345 OF 1990
ALLEGAN COUNTY
DATE APPROVED 5-13-COUNTY REP.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner;

J-1 Set Allegan Co. Mon. (3/4" x 36" pin with cap) on South line of Twp. to the North

Nail & Ottawa Co. Remon. Tag in E side PP N 15°W 8.43'

Nail & Ottawa Co. Remon. Tag in W side 12" Oak S 60° E 81.29'

Nail & Ottawa Co. Remon. Tag in W side 10" Hickory S 30° E 62.06'

Nail & Ottawa Co. Remon. Tag in W side 8" Oak S 10° W 38.45'

On field division E-W; on West edge woods South; Power line West, North 8'±;

Power line East, South 18'±

Ottawa Co. Mon. S 1/4 35, 5-14, East 2.78'

JOHN C BUECHE ห_{อ.} 13027 LAHV

OF MICH

Signed by John C. Bueche, Surveyor's Michigan License No.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1871 REVISED MAY 14, 1975 REVISED JAM., 1983

USE 0006 PAGE 197

Sheet 1 of 2



