

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

22

FOR CORNERS OF -	LOCATED IN -	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 4 N. R. 16 E.	G-8 G-9 H-9
2. PROPERTY CONTROLLING IN SECTION	T. N. R. E.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E.	
4. LOT NO. _____	RECORDED PLAT _____	
5. PRIVATE CLAIMS _____		

LIBR 1 1971

RECORDED

Oct 28 3 00 PM 1971

REGISTER OF DEEDS
 ALLEGAN COUNTY, MICH.

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, DONALD A. BATEMAN do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram over) were, in a field survey on AUGUST 5, 1921, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

G-8 22" BASSWOOD S 29.0'	G-9 26" CHERRY WSW 25.5'	H-9 NW CORNER OF SCHOOL HOUSE
12" MAPLE EAST 17.82'	16" MAPLE ESE 47.2'	SE 82.0'
TEL. POLE WEST 35.55'	TEL. POLE SE 38.10'	14" MAPLE SW 82'
NW COR. HOUSE S 141.55'		
10" WILD CHERRY SW 44.36'		

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner.

G-8 FOUND 3/4" PIPE	G-9 RESET 1" IRON FROM WITNESSES	H-9 FOUND 1/2" BEHOLD
------------------------	-------------------------------------	--------------------------

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-8 22" BASSWOOD S40°E 29.0'	G-9 26" CHERRY S45°W 25.5'	H-9 NW CORNER OF SCHOOL HOUSE
12" MAPLE S85°E 17.82'	16" MAPLE S60°E 47.20'	S 40° E 82.0'
TEL. POLE S85°W 35.55'	TEL. POLE S55°E 38.10'	14" MAPLE S70°W 82'
NW COR. HOUSE S50°E 141.55'	STREET SIGN S75°E 31.4'	28" MAPLE S70°E 101.7'
10" WILD CHERRY S55°W 44.36'		14" MAPLE S30°E 69.3'

116231

Rb 232
116364

Rb 233

SIGNED BY Donald A. Bateman DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 8789

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

PROVED AND SIGNED BY _____ DATE _____

