

**LAND CORNER RECORDATION CERTIFICATE**  
**FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970**

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. <u>4</u> R. <u>16</u> <input checked="" type="checkbox"/>	<u>1-13</u> H-13 H-12
2. PROPERTY CONTROLLING IN SECTION	T. _____ S. _____ R. _____ E. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION	T. _____ S. _____ R. _____ E. _____	_____
4. LOT NO. _____	RECORDED PLAT _____	_____
5. PRIVATE CLAIMS _____	_____	_____

Sec 34

19

FILED

MAY 4 10 56 AM 1972

REGISTER OF DEEDS

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, DONALD A. RATEKIN do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on MARCH 28, 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

<u>1-13</u> OLD NOTES - IRON 36" MAPLE NW 61.8' 12" MAPLE NE 64.4' 4" PEAR SE 73.6'	<u>H-12</u> OLD NOTES - STAKE & IRON 22" MAPLE NW 30.3' 28" MAPLE SW 27.9'	<u>H-13</u> OLD NOTES - IRON IRON E 10.23 13" MAPLE S66.0' 14" MAPLE SW 41.2' 15" MAPLE W 38.6' 16" MAPLE NNW 20.9' 10" W. CHERRY ENE 59.4'
---	---	--

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<u>1-13</u> 5/8" IRON	<u>H-12</u> 1/2" IRON	<u>H-13</u> 1" IRON PIPE
--------------------------	--------------------------	-----------------------------

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>1-13</u> 5/8" IRON ST. SIGN S70°E 40.57' 52" MAPLE N60°W 65.7' SE COR. STORE N45°W 88.42' P. POLE N45°W 42.41' TO MSHD REF. NAIL Rb 243 Rb 451	<u>H-12</u> 1/2" IRON DUNE SCHOONER SIGN POST 6" DIAM. STEEL N75°E 7.80' TEL. UNDERGROUND CABLE OUTLET WEST 23.25' 1/2" IRON E 33' 26" MAPLE N45°W 30.3' 30" MAPLE S75°W 27.8' Rb 244 455	<u>H-13</u> 1" IRON PIPE 1" IRON E 10.23' JOG CORNER NE COR. HOUSE S45°W 80.5' SE COR. RR TIE AT WATER'S EDGE N50°E 60.54' Rb 245 Rb 452 454
---	--	--

SIGNED BY Donald A. Ratekin DATE 4-18-72

SURVEYOR'S MICHIGAN REGISTRATION NO. 8781

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

