

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>21</u>	T. <u>4</u> N. <u>16</u> W.	F-9, F-8
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. _____ E. _____ S. _____ R. _____ W. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ E. _____ S. _____ R. _____ W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

<p>F-9 Found nothing. Set 4" x 36" concrete monument 2,640' at 90° angle to the east section line of 21 as surveyed by Williams and Works in 1927 and in 1949.</p>	<p>F-8 Found 3/4" iron pipe. Recovered with survey notes by Williams and Works, Also by John Clapp.</p>
--	---

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<p>F-9 4" x 36" concrete monument. S 50° W, 4.03', 16" & 20" Twin Oak N 30° E, 5.74', 16" Oak S 85° E, 40.65', 12" Oak S 30° E, 11.71', 14" Oak</p>	<p>F-8 4" x 36" concrete monument. S 30° E, 31.06', 12" Ash S 22° W, 12.41', 12" Maple S 78° W, 21.36', 17" Oak N 60° W, 25.01', 24" Oak</p>
---	--

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Donald L. Bissell (CHIEF OF SURVEY PARTY) DATE 6-22-81
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

PAGE 69