LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 29 N. ●, R. 8 E. ●	L-5;
2. PROPERTY CONTROLLING IN SECTION 13	T. 29 N. ●, R. 8 E. ●	2; 2,M-5
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 7, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

2,M-5
SET 5/8" ROD W/RLS CAP
6" W. PINE S69°W 2.3'
12" CEDAR N13°E 40.0'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

L-5 - FOUND 3/4" PIPE IN 4" SQUARE CONCRETE MONUMENT AT CORNER, ORIGIN UNKNOWN, BUT CONSIDERED BEST AVAILABLE EVIDENCE OF CORNER.
2 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

2,M-5 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR SUBDIVISION OF SECTIONS. EXTENDED SECTION LINE EASTERLY TO U.S. MEANDER LINE, G.L.O. DISTANCE FROM 1/4 CORNER.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-5
FOUND 3/4" PIPE IN CONCRETE
5" CEDAR S36°W 11.4'
6" CEDAR S55°E 16.7'

2
SET 5/8" ROD W/RLS CAP
7" CEDAR N33°E 70.6'
10" R. OAK N34°W 38.2'

STATE OF MICHIGAN
KENNETH J. OSTLING
LAND SURVEYOR
No. 10068
REGISTERED LAND SURVEYOR

SIGNED BY Kenneth J Ostling DATE 10-23-86

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ALPENA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REV. 1975

(A) PLACE SKETCH ON BACK OF ATTACHED SHEET