FEB 1 8 1999

Liber 00003 Page 0029

	· ·	
SECTION	LAND CORNER RECORDATION CER Filing Requirement of Act 74, Mich.	P.A. 1970
For corners in	•	Recorded
ANTRIM	MILTON TOWNSHIP Located In: Corner Code #	12-21-1998 11:35:29
(County)		
1998 REMONUMENTATION		Wanda R∙ Conway
1. Public Land Survey	T 28N R 9W J-3	REGISTER OF DEEDS
	TR T R	
	TR	
2. Property Controlling S	TR	
in Section S	T R	
3. Miscellaneous S		
Property in Sec. S	TR	Register of Deeds Stamp & File Number
I. Lot No, Recorded	Plat	A B C D E F G H I J K L
,		A B C D E F G H I J K L
5. Private Claims		2 - 6 - 5 - 4 - 3 - 2 - 1
	•	3
` .		4 - 7 - 8 - 9 - 10 - 11 - 12
	1	5
RICHARD J. KBAL	, in a field survey on November 19, 19_	98 do
ereby state that under requirement	s of P.A. 74, Michigan P.A. of 1970, the corner	points
nentioned in lines 1 and 2 above w	ere in conformance with regulations and rules theref y instructions of the United States Department of the Ir	nterior 1 1 1
equired in the current manual of surve tureau of Land Management or by a	y instructions of the United States Department of the fi decree of a Court of Law and for that the corner	points 8 19 20 21 22 23 24
nentioned in lines 3, 4 and 5 above to	were in conformance with the rules of the Michigan Bo	pard of 9
and Surveyors or by a Decree of a ecovered, found as expressed below:	a Court of Law; established, re-established, monum	nented, 10 30 29 28 27 26 25
ecovered, toutid as expressed below.		11
IOTE: Not more than 2 comers, all in t	the same town and range, may be recorded	12 31 32 33 34 35 36
on this certificate.		13
 852, Gov't re-survey, set post for 959, Survey by M.C. Feindt, Not 961, Plat of Elkridge Woods, reconsouth 1/4 corner. 984, Survey by A. Lennox (Co. Sorreference to the N. 1/4 cor. 991 & 1992, Survey by N.L. Way 		to the S 1/4 cor. shows South line of Sec. 2, but no reference to the tablished the E. 1/8 line, at the N. line of Sec. 11; no °E, 5.1'; 5" W. Pine, N10°E, 12.45'; 9" R. Pine,
. Description of corner evidence four	nd and/or method applied in restoring or reestablishing of 11, T28N-R9W, Milton Township	
d. 1/2" re-rod in down E-W, fence		·
	nty monument (Berntsten Model G-1 [30" Piston]	with G-2 Cap). Ratified by peer group
d. spike in 7" W. Pine, N06°E, 12		in accordance with
d. spike in 14" Oak, N30°E, 5.10 d. spike in 11" W. Pine , S02°E,		P.O. 345
d. spike in 10" W. Pine, N64°W,		Antrim Co. Chairman
d. 5/8" I.P. in conc. mon. N89°E,	262.62' (R.262.63')	Chilast Senny
	N89°E +/-, 1320' +/-, at E. 1/8 cor. bet. Secs. 2	
lo G.L.O, witnesses were found.	•	Nov. 18, 1998
· ·	er and accessories established to perpetuate locating th <u>k_11, T28N-B9W, Milton Township</u>	ne position of the corner:
d. 1/2" re-rod in down E-W, fence	•	
	nty monument (Berntsten Model G-1 [30" Piston]	with G-2 Cap).
d. spike in 7" W. Pine, N06°E, 12		AND THE PROPERTY OF THE PARTY O
d. spike in 14" Oak, N30°E, 5.10 d. spike in 11" W. Pine , S02°E, 1		GITE OF MICHIGAN
d. spike in 11° W. Pine , 302°C, i d. spike in 10°W. Pine, N64°W, i		S. Can
d. 5/8" I.P. in conc. mon. N89°E,		* RICHARD J. *
	N89°E +/-, 1320' +/-, at E. 1/8 cor. bet. Secs. 2	8.11 ** KRAL **
		* RICHARD J. * KRAL * PROFESSIONAL © SURVEYOR No. 26450
		No.
		26460