

FEB 18 1999

183

Liber 00003 Page 0044

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Antrim  
(County)

Located in: Elk Corner Code #  
Rapids Twp.

ANTRIM COUNTY MI.  
Register of Deeds  
Recorded

12-28-1998 10:20:25

Wanda R. Conway  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

- 1. Public Land Survey Sec. 32 T29N R9W E-12  
T R  
T R  
T R
- 2. Property Controlling S T R  
in Section S T R
- 3. Miscellaneous S T R  
Property in Sec. S T R

- 4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
- 5. Private Claims \_\_\_\_\_

I, Neil L. Way, in a field survey on Dec. 16, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Dec. 1856- GLO set post

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1"x4" iron rod at stone at fence corner running North/South/East/West

Ratified by peer group  
in accordance with  
P.O. 345  
Antrim Co. Chairman

*Arthur L. Lennox*  
Arthur L. Lennox  
Nov. 18, 1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set Antrim County Monument at found 1"x4" iron rod at fence corner

- S65°W 29.23' Maple 6"
- N10°E 6.02' Beech 30"
- N85°E 8.46' Maple 14"
- South 25.28' Maple 30"



Signed by *Neil L. Way*  
Surveyor's Michigan License No. 28432

Date Dec. 17, 1998