

ANTRIM COUNTY
MICHIGAN
RECEIVED FOR RECORD
Nov 30 10 49 AM '95

FEB 22 1996

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

COMMISSION

STAR TWP

Wanda R. Conway
REGISTER OF DEEDS

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|--|--------------|--------------------|
| 1. PUBLIC LAND SURVEY <u>11</u> - T. <u>30</u> N. S., R. <u>5</u> E. W. | | <u>K-3</u> |
| 2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S., R. _____ E. W. | | |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W. | | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Terry B. Smith, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Oct 26, 1995, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on Oct 26, 1995, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

GL0 1839 -- established section post @ 79.94 chains
 Sept. 30, 1975 H. Fluharty set 5/8" re-rod with cap @ intersection of fence
 & per survey by Ed Strotman
 recorded Liber 225 page 90 Antrim County Records.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

found 5/8" iron as described
 replaced with Antrim County Monument

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NE Cor. Sec. 11, T30N, R5W
 set Antrim County Monument
 Red Pine S45E 44.70
 8" Cherry West 11.95
 10" Maple N20W 28.00
 10" Db1. Maple N10E 32.30

Ratified by Peer Group
 in accordance with P.A. 345
 Chairman Arthur L. Lennox
 Date: Oct. 26, 1995


SIGNED BY Terry B. Smith DATE Nov. 29, 1995

SURVEYOR'S MICHIGAN REGISTRATION NO. 25873

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



LIB 302 267

SURVEYOR'S MICHIGAN REGISTRATION NO. _____