LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 30 N. S., R. 6 E. W.	J-7; K-7; L-7; M-7
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 11, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~Description of original monument accepted~~

C. continued

M-7

Fd. 5/8" Re-rod in Ctr N-S Gravel rd.

11" Elm	N67°W	35.76'
11" Maple	N27°W	31.56'
12" Maple Cluster	N34°E	35.22'
Set Cedar Post w/Loc. Tag	Due W.	33'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-7 Accepted Fd. Conc. Mon. by R. Findorff R.L.S. who fd. Iron here in 1969 survey.

K-7 Accepted Fd. Conc. Mon. as estab. by R.L.S., R. Findorff in 1969.

L-7 Fd. & accepted Conc. Mon. as estab. by R.L.S., R. Findorff in 1969.

M-7 Found 5/8" re-rod by R.L.S., R. Findorff, who set Iron from DNR Wit., in 1969 survey. Corner falls in Ctr. of N-S gravel road and is in line with trail road to East.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-7

Fd. 4" round Conc. Mon. & added Cedar Post w/Loc.Tag.

9" Maple	N70°W	31.5'
5" Maple	N46°E	22.5'
8" Maple	S09°E	25.0'

K-7

Fd. 4" Rd.Conc. Mont. & Set Ced. Post w/Loc. Tag.

14" Maple	N59°E	60.7'
5" Cherry	S77°E	56.9'
8" Maple	N02°E	76.6'

L-7

Fd. Round Concrete Mont. & Added Cedar Post w/Loc. Tag

6" Maple	S03°E	7.3'
8" Maple	S75°W	14.4'
7" Maple	N46°E	14.7'
Ctr. N-S Trail Rd.	Due W.	25'±

SIGNED BY Carl F. Roser 6-6-79 DATE

STATE OF MICHIGAN CARL F. ROSER (SEAL) LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

CHESTONIA TOWNSHIP
ANTRIM COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET