

**SURVEY &  
REMONUMENTATION**

**LAND CORNER RECORDATION CERTIFICATE**  
APR 26 1995 FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

**COMMISSION**

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>27</u> T. <u>30</u> <u>N.</u> S. R. <u>7</u> <u>E.</u> W.		<u>I-11</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, S., R. _____, E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, S., R. _____, E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

ANTRIM COUNTY  
 RECEIVED FOR RECORD  
 DEC 5 2 00 PM '94  
 REGISTER OF DEEDS  
 REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Terry B. Smith, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on DEC 13, 1994, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on DEC 13, 1994, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

GLO Corner Post Oct. 1855                      LCRC Liber 001 page 243 by LS #20357  
 Sugar 24 N38E 4                                      June 1978 -- found & witnesses  
 Sugar 10 S38W 14  
 No evidence found

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

found  $\frac{1}{2}$ " iron pipe & witnesses

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-11 -- SE Corne Sec. 27, T30N, R7W  
 Peer group approval Oct. 6, 1994  
 Set Antrim County Monument  
 10" Hemlock N30°E 8.85  
 12" Hemlock South 16.8  
 13" Cedar S45°W 20.2  
 8" Maple N45°W 14.7

Ratified by Peer Group  
 in accordance with P.A. 345  
 Chairman Arthur L. Lennox  
 Date: Oct. 6, 1994

SIGNED BY Terry B. Smith DATE NOV 30, 1994

SURVEYOR'S MICHIGAN REGISTRATION NO. 25873

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR

002 214

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

