

**SURVEY &  
REMONUMENTATION**

**LAND CORNER RECORDATION CERTIFICATE**

APR 26 1995

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

COMMISSION

*Kearney*

Wesley R. Conway  
REGISTER OF DEEDS

JAN 4 11 15 AM '95

ANTRIM COUNTY  
REGISTER OF DEEDS RECORD

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>26</u> T. <u>30</u> N. S., R. <u>07</u> E. W.		<u>K-10</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ N. S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Terry B. Smith, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Dec 20, 1994, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on DEC. 20, 1994, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

GLO Corner Post Oct. 1855

Beech 12 N19 & 18  
Hemlock 10 S3W 25

No evidence found

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Original corner established GLO book and recorded in Liber 001 page 243 dated June 8, 1978. Property owner has constructed a "deer fence" and obliterated the corner. Standard Antrim County Monument set based upon proration from other existing corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-10 E½ Corner Section 26, T30N, R7W  
Peer Group Approval Oct. 6, 1994  
Set Antrim County Monument  
12" Ash East 16.15  
14" Maple N10°W 15.0  
Steel Fence Post S30°E 15.30  
Steel Fence Post N40°W 5.05

Ratified by Peer Group  
in accordance with P.A. 345  
Chairman *[Signature]*  
Arthur L. Lennox  
Date: Oct. 6, 1994

SIGNED BY Terry B. Smith DATE Dec 22 1994

SURVEYOR'S MICHIGAN REGISTRATION NO. 25873

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR



002 235

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_