

**SURVEY &
REMONUMENTATION**

**APR 26 1995 LAND CORNER RECORDATION CERTIFICATE
COMMISSION FILING REQUIREMENT OF ACT 74, MICH. P.A.1970**

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|--|--------------|--------------------|
| 1. PUBLIC LAND SURVEY <u>25</u> T. <u>30</u> N. S. R. <u>7</u> E. W. | | <u>M-11</u> |
| 2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. S., R. _____, E. W. | | |
| 3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. S., R. _____, E. W. | | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

ANTRIM COUNTY
 MICHIGAN
 RECEIVED FOR RECORD
 DEC 5 1 53 PM '94
 REGISTER OF DEEDS
 W. R. Conway
 REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Terry B. Smith, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on NOVEMBER 22, 1994, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on NOVEMBER 22, 1994, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

| | |
|---------------------------|-----------------------------------|
| GLO Corner Post Oct. 1855 | LCRC Liber 002 page 42 |
| Beech 10 N35W 7 | witnesses: N60E 8 white pine 64.5 |
| Beech 9 N36W 25 | N70W Pwr. Pole 69.5 |
| No evidence found | S10W 7" Maple 38.8 |

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

found 3/4" iron bar & witnesses

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-11 -- SE Corne Sec. 25, T30N, R7W
 Peer group approval Oct. 6, 1994
 Set Antrim County Monument
 16" Poplar S70°W 36.8
 8" Red Pine N70°E 64.80
 1/2" iron bar North 33.00
 Utility Pole N70°W 69.10

Ratified by Peer Group
 in accordance with P.A. 345
 Chairman Arthur L. Lennox
 Date: Oct. 6, 1994


SIGNED BY Terry B. Smith DATE NOV. 30, 1994

SURVEYOR'S MICHIGAN REGISTRATION NO. 25873

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR



1995 002 219

SURVEYOR'S MICHIGAN REGISTRATION NO. _____