

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Liber **00003** Page **0153**

For comers in "ECHO TWP"

<u>ANTRIM</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>31N</u> R <u>7W</u>	B-5
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

ANTRIM COUNTY MI.
 Register of Deeds
 Recorded

12-21-2000 11:09:53

Manda R. Conway
 REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

I, NEIL L. WAY, in a field survey on DEC. 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 comers, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-5 N 1/4 CORNER SEC. 18
 GLO SET CORNER POST 1857. A 3 1/2" IRONWOOD STAKE.
 SUGAR 16 N64 1/2 W 19L
 SUGAR 11 S61 1/2 W 13 L
 NO OLD CORNER
 CHURCH FOUND OLD STAKE AND BURNED OFF WIT'S, MAY 5, 1909
 BEECH 6 N58 1/2 W 19L
 BEECH 12 N44 1/2 E 15 L
 BEECH 3 S13 W 4 L

**SURVEY &
 REMONUMENTATION**

JAN 23 2001

SECTION

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-5 N 1/4 CORNER SEC. 18
 FOUND IRON BAR AND CAP #28417 AS SET BY ROBERT MITCHELL JUNE 28, 1999 BY SINGLE PRORATION MEASUREMENT FROM GOV'T. SURVEY RECORD.
 N73W 19.27' BASSWOOD 18"
 S50W 8.12' MAPLE 6"
 S85E 31.83' MAPLE 8" TW.
 N57E 43.67' MAPLE 12'

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-5 N 1/4 CORNER SEC. 18
 ACCEPTED MITCHELL IRON AS CORNER, REMOVED IRON AND REPLACED WITH COUNTY MONUMENT.



N73W 19.27' BASSWOOD 18"
 S50W 8.12' MAPLE 6"
 S85E 31.83' MAPLE 8" TW
 N57E 43.67' MAPLE 12"
 NORTH 10' E-W TRAIL ROAD

Ratified by Peer Group
 In accordance with
 P.A. 345
 Antrim Co. Chairman

Arthur L. Lennox
 Arthur L. Lennox, P.E., P.S.
 Nov. 28, 2000

Signed by Neil L. Way
 Surveyor's Michigan License No. 28432

Date Dec. 18, 2000