

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Liber **00003** Page **0145**

For corners in "ECHO TWP"

<u>ANTRIM</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>31N</u> R <u>7W</u>	F-5
	T ___ R ___	_____
	T ___ R ___	_____
	T ___ R ___	_____
2. Property Controlling in Section	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____
3. Miscellaneous Property in Sec.	S ___ T ___ R ___	_____
	S ___ T ___ R ___	_____

ANTRIM COUNTY MI.
 Register of Deeds
 Recorded

12-21-2000 11:03:05

Honda R. Conway
 REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, NEIL L WAY, in a field survey on DEC. 18, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5						●							
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

F-5 N 1/4 CORNER SEC. 16
 GLO SET CORNER POST 1857

SUGAR 12 N45 E 25 L
 BEECH 8 N52 3/4 W 27L

JOHN FERGUSON #24595, CERT. JAN 7, 1985 SET A T IRON.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-5 N 1/4 CORNER SEC. 16
 FOUND T IRON AS STATED ABOVE.

**SURVEY &
 REMONUMENTATION**

JAN 23 2001

SECTION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-5 N 1/4 CORNER SEC. 16

**ACCEPTED T IRON AS CORNER, REMOVED AND
 REPLACED WITH COUNTY MONUMENT.**

S50W 22.83' MAPLE 12"
 N60W 27.35' MAPLE 10"
 N70E 30.59' CHERRY 14"
 S05W 31.37' MAPLE 12"

Ratified by Peer Group
 In accordance with
 P.A. 345
 Antrim Co. Chairman

Arthur L. Lennox

Arthur L. Lennox, P.E., P.S.
 Nov. 28, 2000



Signed by *Neil L. Way*
 Surveyor's Michigan License No. 28432

Date DEC. 18, 2000