LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in ARENAC	Localed in: Co	orner Code =##	
(County)	Cocateu III.	omer Code -++	
Public Land Survey ,	T R	G-7,H-7 I-6,I-7	
	T R		
3. Miscellaneous S	τR	Registo	er of Deeds Stamp & File Number
4. Lot No, Reco	rded Plat		A B C D E F G H I J K L
5. Private Claims		2	6-6-4-3-2-1
		a	
CARL KIISKILA in	a lield survey onAUGUST 14	19 95 6	
above were in conformance with the Court of Law; established, re-es expressed below: NOTE: Not more than 4 corne on this certificate.	urt of Law and/or that the corner points in a rules of the Michigan Board of Land Stablished, monumented, re-monumented, re-monumenter, all in the same town and range town and accessories and/or sub-	urveyors or by a Decree of a patential, recovered, found as 10 page 11 page 12 page 13 page 14 page 15	
	, B.T'S, LINE TREES & TOPOGRAPHY, INE MOTES; UNLESS NOTED IN ITEM "B"		CARL KIIGKILA LAND SURVEYOR No. 33981
. ;	nce found and/or method applied	in restoring or reestablishing cor	DOLLAND SURVEY
6-7	H-7	1-6	1-7
FD 1/2" BAR FOR THE SW CORNER OF SEC 15. CORNER WAS FD AND ACCEPTED BY D. LEDY P.S, AND T. LAPHAM P.S. CTR N-S GRAVEL RD IS 11' WEST.	FD AND ACCEPTED 1/2° BAR FOR THE S 1/4 CDR OF SEC 15 AS SET BY DUANE LEDY P.S, RECORDED PER ACT 74,PA 1970 IN LIBER 1, PAGE 287. CORNER IS MIDWAY AND ON LINE BETWEEN FOUND SEC CORNER TO WEST AND REESTABLISHED SEC CORNER TO THE EAST.	FOUND AND ACCEPTED BY D. LEDY	REESTABLISHED SE COR OF SEC 15 AT A POSITION CALCULATED PER DUANE LEDY'S PS, PROPORTIONATE MEASUREMENTS (PER L.C.R.C. RECORDED IN LIBER 1, PG 287). COR FN POST 1S 20'S AND 10'E, FN TO SOUTH AND WEST.
C. Description of monument fo	or corner and accessories establis	hed to perpetuate locating the po	osition of the corner:
6-7 FOUND 1/2" BAR BENT, REPLACED WITH 5/8" X 32" REROD W/CAP.	H-7 FD 1/2" BAR WITH CAP. #5" N. OAK \$26°W 21.59'	I-6 FOUND 1 3/4° PIPE, SET CEDAR POST AND TAG 33' N.	I-7 SET 5/8* REROD FOR THE SE COR OF SEC 15 PER D. LEDY
12" DAX N65°E 33.65° 8" DAX S58°E 33.26° RR TJE FN POST N81°N 19.15° 9" DAX S41°N 101.37°	**12" DAK N14°E 57.71' **14" R. PINE N89°E 33.56'	#P. POLE N20°E 41.44' 16" TWN DAK N67"W 73.83' 16" DAK 568°W 102.70'	12° OAK \$77°N 8.56° 12° OAK N31°N 38.38°
9" QAK S41°N 101.37"	BEND TO EAST. \$ LEDY WITNESS - L1 1, PG 287	6" DAK S32°E 50.16' CTR E-N GRAVEL RD SOUTH 5' CTR DIRT RD TO S. WEST 75'	6° DAK N80°E 59.23' 14° DAK 537°E 10.65' COR FN POST 521°E 21.7'
,	## J.SRAMGER #16041, WITNESS.	# TIM LAPHAM WITNESS	CTR N-S 2 TRACK RD IS 28' E.
Signed by Carl Till	ideila 33981		-95
Signed by)	Date	•
ourveyor's Michigan License No	J	FORM APPROVED I	IY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1 REVISED MAY 14, 1 REVISED MAY 14, 1