

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>36</u> T. <u>20</u> N. R. <u>3</u> E.		<u>K-11; L-11; M-11</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ S. R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ S. R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER \_\_\_\_\_

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on FEBRUARY 24, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:


- K-11 FOUND CONCRETE MONUMENT USED AS SECTION CORNER IN PLATS OF FOREST GROVE IN SECTION 25.
- L-11 SET BY SINGLE PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS. NO EVIDENCE OF PREVIOUS CORNER.
- M-11 FOUND CONCRETE MONUMENT AT CORNER AS USED IN CONTROLLING FOREST GROVE PLATS IN SECTION 25. BEST AVAILABLE EVIDENCE.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>K-11</u>	<u>L-11</u>	<u>M-11</u>
LEFT CONCRETE MONUMENT IN PLACE	SET DNR MONUMENT	LEFT CONCRETE MONUMENT IN PLACE
12" B. OAK S48°E 40.8'	3" W. PINE S41°W 10.4'	N. CALDWELL WITNESSES
4" B. OAK S64°W 53.1'	14" TW. R. OAK S75°E 21.3'	5" R. OAK S40°W 9.1'
		12" R. OAK N45°E 55.5'

SIGNED BY *Kenneth J. Ostling* DATE 9

SURVEYOR'S MICHIGAN REGISTRATION NO. #10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ ARENAC COUNTY