

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>20</u> N. R. <u>5</u> E.	<u>H-9</u>
2. PROPERTY CONTROLLING IN SECTION <u>22</u>	T. <u>20</u> N. R. <u>5</u> E.	<u>4; 5; 6</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S. R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 12, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 1-9 Set corner in centerline E-W road, in line with fence S. This conforms with Co. Surveyor record for porportionate measurement and fits subdivision of Section 22.
- 4 Set by standard survey procedure for the subdivision of sections.
- 5 Set by standard survey procedure for the subdivision of sections.
- 6 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 6" Iron w/RLS Cap Nail in 24" Maple N56°W 79.53 Nail in PP N21°E 66.22	Set 5/8"x40" ⁴ Iron Bar w/RLS Cap and Cedar Post 4" W. Pine S84°W 8.3 15" Oak N43°E 19.3	Set 5/8" Rod ⁵ w/RLS Cap & Cedar Post 3" Oak S88°E 20.25 6" Oak N33°E 32.1
6 Set 5/8"x40" Iron Bar w/RLS Cap & Cedar Post 4" W. Birch N78°W 26.6 5" W. Pine N01°W 31.8		

SIGNED BY Kenneth Ostling DATE 8/24
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ ARENAC COUNTY