

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. 20 N. R. 5 E.	G-6; I-6
2. PROPERTY CONTROLLING IN SECTION 15	T. 20 N. R. 5 E.	7; 10
3. MISCELLANEOUS PROPERTY IN SECTION_____	T. _____ N. S. R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 11, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 6 Set corner at old fence intersection N & W, which appears as best available evidence of proper location for corner.
- 6 Set corner at apparent fence intersection corner post which falls in proper location from Co. Surveyor NBT stump remains. Fits Co. Surveyor record for measurement and alignment.
- 7 Set by standard survey procedure for the subdivision of sections.
- 10 Set by standard survey procedure for the subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-6	I-6	7
Set DNR Mon. & Cedar Post	Set DNR Monument	Set 5/8" Rod w/Cap & Cedar Post
4" W. Pine N60°E 33.9	5" Maple N34°W 16.95	3" W. Pine S79°E 2.85
4" W. Pine N01°E 52.25	8" Maple N05°E 20.7	4" W. Pine S85°W 4.55
	10	14" Tw.Maple N09°E 10.55
	Set 5/8" Rod w/RLS Cap & Cedar Post	
	3" R. Pine N26°E 30.35	
	5" R. Pine S89°E 27.55	

SIGNED BY Kenneth J. Ostling  
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

DATE 8/24/79



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY  
 APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

ARENAC COUNTY