

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____ T. <u>20</u> N. <u>X</u> , R. <u>7</u> E. <u>X</u>		<u>I-3, J-3</u>
2. PROPERTY CONTROLLING IN SECTION <u>11</u> , T. <u>20</u> N. <u>X</u> , R. <u>7</u> E. <u>X</u>		<u>Code 1</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ N. _____, R. _____ E. _____		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 4-23-73 19\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_ 19\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- I-3** Set corner by double proportionate measurement between corner one mile East, 2 miles West, One mile South, and 1/2 mile North. Nothing evident for a previous corner.
- J-3** Set corner by proportionate measurement between restored section corners. Nothing for a previous corner.
- Code 1** Set corner by standard survey procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NW Sec. cor. I-3	N 1/4 cor. J-3	Code 1
Set DNR Monument	Set DNR Monument	W 1/16 cor on North sec. line
7" W. Ash S32 W 15.8'	5" W. Ash S56E 19.3'	Set 3' of 1" pipe
7" Crooked Maple S81 E 19.1'	32" trp. Maple S31W 15.55'	10" W. Ash S40E 20.6'
		8" Y. Birch S49W 8.2'

SIGNED BY Kenneth J. Ostling DATE 5-73  
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:  
 SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY  
 APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)