

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

BARAGA CO.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>48</u> ^{N.} X , R. <u>31</u> ^{W.} X	<u>H8, G7</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____, N. _____, S. _____, R. _____, E. _____, W. _____	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____, N. _____, S. _____, R. _____, E. _____, W. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 23, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner H8: Found narrow gauge rail road rail. Local people believe work to have been done by mining company.

Corner G7: Original monument and accessories not found. Found 1-1/2" I.D. Iron pipe with 6" cap. Believed to have been set by M.S.H.D.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner H8: Established at iron rail.

Corner G7: Restored at iron pipe.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner H8: Narrow gauge rail road rail.
 8" Sugar S70°E 19.80 ft.
 9" Sugar S40°W 14.55 ft.
 12" Sugar N70°W 10.00 ft.

Corner G7: 1-1/2" I.D. iron pipe with 6" cap.
 DNR tag and nail in:
 10" Oak S15°W 13.55 ft.
 4" Sugar N20°W 16.30 ft.
 6" Maple S60°E 17.60 ft.

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2/4/80

CHIEF OF SURVEY PART
 MICHIGAN REGISTERED LAND SURVEYOR
 Keith L. Sackett
 Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

