

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

BARAGA CO

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. <u>48</u> ^N XX , R. <u>31</u> ^{XX} W .	G8
2. PROPERTY CONTROLLING IN SECTION <u>21</u> ^{q.w.t.}	T. <u>48</u> ^N XX , R. <u>31</u> ^{XX} W .	14
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____, R. _____	
4. LOT NO. _____	RECORDED PLAT _____	
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 23, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 14: Found narrow gauge railroad rail driven in ground. Set by unknown persons.

Corner G8: Original monument and accessories not found. Found mushroom topped 1" iron pin and square post.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 14: Restored at rail iron.

Corner G8: Restored at iron pin.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 14: Narrow gauge railroad rail buried in ground. DNR ref. tag and nail in:
 8" Sugar S16°E 21.50 ft.
 6" Sugar N82°W 17.80 ft.
 Cluster of 4-6" Maples N18°E 38.60 ft.

Corner G8: 1" iron pin with mushroom shaped top.
 8" Sugar S83°E 17.6 ft. 1/4 S, NBT
 10" Sugar S18°W 46.3 ft. 1/4 S, NBT
 8" Sugar N76°W 32.6 ft. 1/4 S, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE _____

CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett
 Michigan Dept. of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

