LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

1. PUBLIC LAND SURVEY T. 48 S., R. 32 K. 2. PROPERTY CONTROLL. N. S., R. W. 3. MISCELLANEOUS PROPERTY IN SECTION T. S., R. W. 4. LOT NO. RECORDED PLAT 5. PRIVATE CLAIMS REGISTER OF DEEDS STAMP AND FILING NUMBER I, Keith L. Sackett Meeting that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on March 22, 19 78, established, re-established, monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3, 4 and 5 above were, in a field survey on 19 mentioned in lines 3 and 5 above were, in a field survey on 19 mentioned in lines 3 and 5 above were, in a field survey on 19 mentioned in lines 3 and 5 above were, in a field survey on 19 mentioned in lines 10 mentioned in lines
3. MISCELLANEOUS PROPERTY IN SECTION, T
3. MISCELLANEOUS PROPERTY IN SECTION, T
I. Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey onMarch 22,, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on, 19, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law: A. Description of original monument and accessories and/or subsequent restoration:
I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on
the corner points mentioned in lines 1 and 2 above were, in a field survey on restablished, monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on
the corner points mentioned in lines 1 and 2 above were, in a field survey on restablished, monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on
A. Description of original monument and accessories and/or subsequent restoration: Original monument and accessories not found.
Original monument and accessories not found.
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
Corner re-established on line and midway between section corners N-S.
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
Set 1" I.D.x36" Iron Pipe with
aluminum cap
6" Spruce N46W 27.8 ft. 4S, NBT 5" Spruce N39E 5.0 ft. 4S, NBT
P. Pole 201 S36E 53.2 ft.
SIGNED BYDATE
SURVEYOR'S MICHIGAN REGISTRATION NO
FOR STATE AND UNITED STATES AGENCIES:
SIGNED BYDATE
DATE July PART July BALL 918 11 11 11 11 11 11 11 11 11 11 11 11 1
APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR Keith L. Sackett SACKETT
Department of Natural Resources LAND SURVEYOR
SURVEYOR'S MICHIGAN REGISTRATION NO. 19006 NO. 19006 19006

MAY PLACE SKETCH ON BACK OF ATTACHED SHEET