

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

<u>Sarasota</u> (County)	Located In:	Corner Code -#
1. Public Land Survey	T 49N — R 2W	
	T — R	
	T — R	
	T — R	
2. Property Controlling in Section	S 32 — T — R	5
	S — T — R	9
3. Miscellaneous Property in Sec.	S — T — R	12
	S — T — R	9
4. Lot No. _____	Recorded Plat _____	
5. Private Claims _____		

Register of Deeds Stamp & File Number

I, Keith Sackett, in a field survey on October 15, 19 88, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	6	5	4	3	2	1						
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

A. Description of original monument and accessories and/or subsequent restoration:

<u>5</u>	<u>8</u>	<u>12</u>	<u>9</u>
Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.	Not set on original survey nor subsequently, apparently.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

<u>5</u>	<u>8</u>	<u>12</u>	<u>9</u>
Established during section subdivision.	Established during section subdivision.	Established during section subdivision.	Established during section subdivision.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>5</u>	<u>8</u>	<u>12</u>	<u>9</u>
Set 1" x 36" I.P. w/4" aluminum cap.	Set 1" x 36" I.P. w/4" aluminum cap.	Set 1" I.B. x 32" I.P. w/4" aluminum cap.	Set 1" x 36" I.P. w/4" aluminum cap.
4" sugar N13W 28.1' 1/16s BT	6" w. pine S10W 22.9' 1/16s BT	10" w. pine S57E 15.4' 1/16s BT	8" sugar S83W 10.8' 1/16s BT
16" cedar S62E 27.5' 1/16s BT	10" sugar S45E 18.1' 1/16s BT	8" cedar S34W 21.8' 1/16s BT	4" sugar N01W 11.2' 1/16s BT
4" sugar S72W 19.8' 1/16s BT	10" sugar N24E 21.6' 1/16s BT	5" cedar N69W 13.1' 1/16s BT	8" sugar S74E 10.2' 1/16s BT

Signed by

Keith Sackett

Date

12-9-88

Surveyor's Michigan License No.

19006