

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

BARAGA COUNTY

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 49 N. X. R. 32 X. W.	I-3
2. PROPERTY CONTROLLING IN SECTION	T. 49 N. X. R. 32 X. W.	3
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S. R. E. W.	
4. LOT NO. ---, RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-3-, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:
**Corner I-3: Original monument and accessories not found,
 Found 1 3/8" ID Iron Pipe by unknown length set by Norman Thompson, R.L.S.**

Corner 3: Found 1 3/8" I.D. by unknown length Iron Pipe set by Norman Thompson, R.L.S.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner I-3: Restored at Norman Thompson Iron Pipe.

Corner 3: Restored at Norman Thompson Iron Pipe.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**Corner I-3: 1 3/8" I.D. Iron Pipe 18" out of ground.
 6" Sugar S9W, 9.6 ft. S10, NBT
 12" Sugar N78E, 21.1 ft. S2, NBT
 6" Sugar N50W 11.1 ft. S3, NBT**

**Corner 3: 1 3/8" I.D. Iron Pipe 18" out of ground.
 16" cedar S02E 24.6 ft. 1/16S, BT
 10" Cedar N55W, 29.6 ft. 1/16S, BT
 12" Cedar N77E, 25.7 ft. 1/16S, BT**

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2-16-83

CHIEF OF SURVEY PARTY
 MICHIGAN REGISTERED LAND SURVEYOR

Keith L. Sackett
 Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006