LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

BARAGA COUNTY

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. ____ N. S., R. ____ E. W.	
2. PROPERTY CONTROLLING IN SECTION 30	,T. 50 N. ~~S.~~, R. 33 ~~E.~~ W.	2, 1
3. MISCELLANEOUS PROPERTY IN SECTION ____	,T. ____ N. S., R. ____ E. W.	

4. LOT NO. ____ , RECORDED PLAT ____

5. PRIVATE CLAIMS ____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 15, 19 81, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of Law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner 2: Not set on original survey nor subsequently apparently.

Corner 1: Not set on original survey nor subsequently apparently.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 2: Established on line and midway between ¼ corner west and section corner east.

Corner 1: Established on line and proportion distance between ¼ corner east and section corner west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 2: Set 1" I.D.x32" iron pipe with 4" alum. cap.
5" Sugar N30E 11.0 ft. 1/16S,BT
4" Maple S63E 13.0 ft. 1/16S,BT
14" Sugar S52W 5.8 ft. 1/16S,BT

Corner 1: Set 1" I.D.x32" iron pipe with 4" alum. cap.
5" Spruce S64E 51.6 ft. 1/16S,BT
22" W. Pine N45E 55.5 ft. 1/16S,BT
16" Maple N73W 59.4 ft. 1/16S,BT

SIGNED BY ____ DATE ____

SURVEYOR'S MICHIGAN REGISTRATION NO. ____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ____ DATE ____

APPROVED AND SIGNED BY Keith L. Sackett (CHIEF OF SURVEY PARTY / MICHIGAN REGISTERED LAND SURVEYOR) DATE 1-28-82

Keith L. Sackett
Michigan Dept. of Natural Resources

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET