

SURVEY & REMONUMENTATION

APR 26 1995

COMMISSION

For corners in

Baraga

(County)

Located in:

51N 30W

Corner Code #

E-13

- | | | | | | |
|------------------------------------|---|-------|---|-------|-------|
| 1. Public Land Survey | T | _____ | R | _____ | _____ |
| | T | _____ | R | _____ | _____ |
| | T | _____ | R | _____ | _____ |
| | T | _____ | R | _____ | _____ |
| 2. Property Controlling in Section | S | _____ | T | _____ | R |
| | S | _____ | T | _____ | R |
| 3. Miscellaneous Property in Sec. | S | _____ | T | _____ | R |
| | S | _____ | T | _____ | R |

RECEIVED FOR RECORD THIS 19TH DAY OF DECEMBER, A.D. 1994 AT 9:00 A.M. AND RECORDED IN LIBER 4 OF LAND CORNER RECORDATION ON PAGES 525-526.

Theda J. Robillard

BARAGA COUNTY REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Michael Mileski

December 94

I, _____, in a field survey on _____, 19____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

E-13; Section Corner common to Sections 32 and 33, T51N, R30W; on 5th Correction Line.

See back of form.

APPROVED LAND CORNER
P.A. 345 OF 1990
Baraga County

12-9-94



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-13; Section Corner common to Sections 32 and 33, T51N, R30W, on 5th Correction Line.

Found Mr. Schmeling's 1" x 48" galvanized iron pipe with stamped 4" brass cap projecting 18" above ground to be in agreement with both his witnesses of record the condition of each as described in Part A. I did not remonument the corner. Accepted found monument as a careful and faithful perpetuation of the position of original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-13; Section Corner common to Sections 32 and 33, T51N, R30W, on 5th Correction Line.

Found 1" x 48" galvanized iron pipe with stamped 4" brass cap.

Set 60d spike	SW/side	6" Yellow Birch	N15°E	13.04'
Set 60d spike	SE/side	14" Hemlock	S55°E	35.38'
Set 60d spike	S/side	17" Hemlock	S15°E	22.41'
Set 60d spike	S/side	8" Sugar Maple	N69°W	12.90'

All of the above new bearing trees marked with upper and lower face blazes and scribed "NBT".

Signed by Michael Mileski Date 19 December 1994
Surveyor's Michigan License No. 39091

A. Description of original monument and accessories and/or subsequent restoration:

E-13; Section Corner common to Sections 32 and 33, T51N, R30W, on 5th Correction Line.

Originally established during U.S. Survey conducted by Austin Burt, D.S. in 1845 and monumented with a wood post witnessed by a

Sugar 10 N18°E 31 lks. (Gone)
and a
Sugar 10 N38°W 19 lks. (Gone)

The late Norman Thompson, RLS #4348 states in his field notes dated 31 July 1945 (copies of which were obtained from Northern Hardwoods' office in L'Anse) that the northwest U.S. bearing tree was alive and 18" in diameter. Mr. Thompson set a hemlock post and noted the following new bearing trees:

Hemlock 8 N31°E 25.5' (Gone)
and a
Hemlock 12 N08°W 20.0' (Gone)

According to a Land Corner Recordation Certificate filed by Robert Schmeling, P.S. # 8317 and recorded in Liber 1 on page 171 during the course of a field survey conducted on 25 September 1974 Mr. Schmeling recovered Mr. Thompson's hemlock post in agreement with Mr. Thompson's new bearing trees both of which were down and in an advanced state of decay with partial scribing evident on each. Mr. Schmeling set a 1" x 48" galvanized iron pipe with 4" brass cap appropriately stamped as to location and noted the following new bearing trees:

Red Maple 6" N65°W 6.0' to CL
(Presently alive and 11" in dia. - Set 60d spike SW/side N63°W 6.00')

and a

Hemlock 8.5" N33°E 19.5' to CL
(Presently alive and 14" in dia. - Set 60d spike SE/side N31°E 19.50')