

SURVEY & REMONUMENTATION

FEB 17 1998



2636 Page: 1 of 1 12/16/1997 12:15P

Sandy Schondelmayer - Barry Co. LCRCR

BARRY COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For Corners in BARRY CO. Located In: Corner Code #
1. Public Land Survey CENTER 1/4 COR SEC.16 HOPE TWP. T..2N R..9WF-6.....
2. Property Controlling in Section S.....T..... R..... S.....T..... R.....
3. Miscellaneous Property in Sec. S..... T..... R..... S..... T..... R.....
4. Lot No....., Recorded Plat.....
5. Private Claims.....

Register of Deeds Stamp & File Number

Grid table with columns A-M and rows 2-13. A dot is present at the intersection of column F and row 6.

I, RAYMOND MOORED, in a field survey on SEPT. 10, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4, and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration: CORNER NOT ESTABLISHED BY GLO NO CORNER HISTORY AVAILABLE.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: FOUND 1/2" IRON AS ESTABLISHED BY B. REYNOLDS, P.S. REMOVED IRON AND SET STANDARD BARRY COUNTY REMONUMENTATION IRON WITH CAP.

ACCEPTED POSITION AS THE BEST AVAILABLE EVIDENCE OF THE POSTION OF THE CORNER.

APPROVED BY BARRY COUNTY REMONUMENTATION PEER GROUP ON 18 Nov '96 [Signature]

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: SET STANDARD BARRY COUNTY REMONUMENTATION IRON WITH CAP -NAIL & TAG IN E SIDE 12" HICKORY WEST 23.84' -NAIL & TAG IN E SIDE 12" HICKORY S50W 47.18' -NAIL & TAG IN W SIDE 10" PINE S65E 36.37' -NAIL & TAG IN W SIDE 10" PINE S35E 46.65'

Signed by [Signature] Surveyor's Michigan License No. 26463

Date: 12/11/97

