SURVEY & REMONUMENTATION

AUG 3 1 1994

COMMISSION

on this certificate.

BARRY COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE

Eiling Requirement of Act 74 Mich D.A. 1070

For corners in		rining nequirement of Act 74, with P.A. 1970								~	_				
	BARRY		Located	d In:	Corn	er Code <u>+</u> #					mday S ECIST			-	į
1.	Public Land Survey		ŌRA	10W I-6 NGEVILLE TWNSP. EGR. SEC. 14 & 15				4							
2.	Property Controlling in Section			R R					,						
3.	Miscellaneous	s	T	R				Registe	er of I	ehaa(Stame	. & Fi	le Ne	ımher	
	Property in Sec.	s	T	R			<u></u>							,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_
4. 5.	, , , , ,	cordec	Plat	-					A B	C D	E F	G F		J K	-
					•			3		++	-	+-+		+-+-	_
do in cu Ma ab Co	BRIAN REYNOLDS, thereby certify that under requirens 1 and 2 above were in a trent manual of survey instructionagement or by a decree of a cove were in conformance without of Law; established, re	irement conform ctions of Court of the rule	s of P.A. 74 nance with the United Law and/o as of the Mi	, Michigan P regulations d States Dep r that the cor chigan Board	A. of 1970, the and rules the partment of the rnerpoints me d of Land Sun	corner points marefore as required interior, Bureau ntioned in lines 3 reyors or by a De	entioned ed in the u of Land 3, 4 and 5 coree of a	4 5 6 7 8 9	18- 19-	817	91621	10)—————————————————————————————————————	14	
ex	pressed below:							10	30-	29	28	27	<u>-</u>	26	-

A. Description of original monument and accessories and/or subsequent restoration:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded

- G.L.O.: SYLVESTER SIBLEY D.S., 1827, (R10W, Pg. 81):

W. OAK - 9 - S39W - 122; Do. - 8 - N70E - 55.

- A.C. WILLSON, 24 APR 1867, (L.2, Pg.137): SET STONE & BRICK.
- LEE S. COBB, 1895, (L.2, Pg.283): FOUND STAKE & STONE 26x14x9 WITH CROSS ON TOP; W.OAK - 16 - S70 3/4W - 78 1/2.
- L.C.R.C. # 135: JAMES L. KING, 11 APR 1974:

ESTABLISHED CORNER FROM LOCAL OCCUPATION. (SEE BACK FOR WITNESSES)

- L.C.R.C. # 165: JAMES L. KING, 9 APR 1974:

RE-ESTABLISHED CORNER BY PRORATION OF EXISTING OCCUPATION WATHIN SECTION.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- FOUND 1/2" IRON IN MONUMENT BOX AT THE INTERSECTION OF KELLER & NORRIS ROADS.

ACCEPTED AS BEST AVAILABLE EVIDENCE OF CORNER LOCATION

ACT 345 BARRY COUNTY REMONUMENTATION APPROVED BY PEER REVIEW AT A MEETING HELD ON

BRIAN REYNOLDS

UNE

STATE OF MICHIGAN COUNTY OF BARRY RECEIVED FOR RECORD

JUL 8 12 42 PM "94

- Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 - SET BARRY Co. REMONUMENTATION MONUMENT IN MONUMENT BOX:
 - SW. CORNER OF EASTERNMOST TELEPHONE RISER N50E 66.29'
 - CENTER TOP CONCRETE R/W MARKER S20E 106.19'
 - FND. NAIL & CAP SE, FACE 28" BLACK WALNUT N45E 67.30'
 - P.K. & SHINER SW. SIDE UTIL. POLE N40W 223.98'
 - -P.K. & SHINER W. SIDE UTIL, POLE N17E 99.32'
 - CENTER TOP CONCRETE R/W MONUMENT S68E 88.87'
 - -P.K. & SHINER E. SIDE 20" BLACK WALNUT S16W 111.03'
 - P.K. & SHINER W. SIDE 20" BLACK WALNUT S18E 102.69'

Signed by _ 31602 - Surveyor's Michigan License No.

OF MICH BRIAN REYNOLDS LAND SURVEYOR NO. 31602 CAND S

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983

- L.C.R.C. 135, JAMES L. KING, 11 APR 1974:
MONUMENT BOX:
STEEL FENCE POST - N45W - 46.4'
SW CORNER TELE, STANCHION - N50E - 64.13'
CENTER OF CONCRETE R/W MONUMENT - S20E - 106.2'

the section than the section with the

The Highidian Comment

SHE STORY STA

- * 15 59 De 1

- L.C.R.C. 165, JAMES L. KING, 9 APR 1974: 1/2" IRON IN MONUMENT BOX: STEEL FENCE POST - N45W - 46.4' TELEPHONE CABLE STANTION - N50E - 64.13'

SURVEY & REMONUMENTATION

AUG 3 1 1994

COMMISSION