

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	<u>33-34</u> , T. <u>3</u> N. <u>10</u> E. R. <u>10</u> W.	<u>I-13, E-13, I-12</u>
2. PROPERTY CONTROLLING IN SECTION	<u>33-34</u> , T. <u>3</u> N. <u>10</u> E. R. <u>10</u> W.	<u>G-13, G-12</u>
3. MISCELLANEOUS PROPERTY IN SECTION	_____, T. _____ N. _____ S. R. _____ E. _____ W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Dwayne Scott, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on December, 1975, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- SE 34 I-13 Recovered 1- $\frac{1}{4}$ " Solid Iron Rod, N. Edge Dirt Road
 - SW 33 E-13 Recovered $\frac{1}{2}$ " Iron Rod in Conc., Rod is 3" above ground in fence corner with fences going N. and E., Plastic Cap #12029
 - E 1/4 34 I-12 Recovered 1- $\frac{1}{4}$ " Iron Pipe in Conc. 10" below ground, found with Metal Detector, Placed $\frac{3}{4}$ " pipe inside 1- $\frac{1}{4}$ " pipe and Cap #12029 raised to surface.
 - SW 34 G-13 Set 4" x 30" Conc. Mon. w/alumn. cap, Set Cor. on Twp. line and single prop. Dist. from Sec. Cors. E. and W.
 - W 1/4 34 G-12 Set 4" x 30" Conc. Mon. w/alumn. cap, Set according to Gov't ties to the north and line of Occ. to the East.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-13 1- $\frac{1}{4}$ " Solid Iron Rod S36°E 24.20' 8" Oak S21°W 19.38' 5" Oak N87°W 42.75' 32" Oak	I-12 1- $\frac{1}{4}$ " Iron Pipe in Conc. w/ $\frac{3}{4}$ " pipe and Cap #12029 S43°W 71.81' 12" B. Oak N47°E 36.3' SW Cor. David B. Watson headstone in cemetery. S74°W 6.0' 48" B. Oak Stub 16' high S83°E 25.44' 52" B. Oak	G-13 4" x 30" Conc. Mon. w/alumn. cap N47°W 28.55' 19" B. Oak S61°W 35.84' 14" W. Oak N10°E 14.70' 6" B. Oak East 16.5' Conc. Mon. NW Corner Sec. 3 G-12 4" x 30" Conc. Mon. w/alumn. cap S80°W 35.32' 20" Box Elder N49°E 38.82' 18" Oak S42°E 35.98' 16" Oak
--	--	--

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Dwayne Scott CHIEF OF SURVEY PARTY DATE Jan 1976
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 12029