

# LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>4N</u> N. S., R. <u>9W</u> E. W.	<u>B-3, C-3, B-1</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. S., R. _____ E. W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

No. 255

FILED

DEC 29 1978

**HOWARD J. FERRIS**  
Barry County Register of Deeds  
At 10:55 AM

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Douglas W. Bonnema, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 7, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-3 Set corner on $\phi$ B.T. road and on line with fences to N and S.	C-3 Set corner on $\phi$ B.T. road and on line with fence to S.	B-1 Set corner 14.52' W of S 1/4 corner, Sec. 31, T5N, R9W, per previous information from Williams & Works, Inc.
--	---	--

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-3 Capped re-rod <u>N 1/4 Cor 7</u> Nail in sde 16" Oak SSE 29.22' PK in sde fence post North 22.08' Nail in sde 12" W. Cherry ESE 210.20'	C-3 capped re-rod Nail in sde 16" Oak WSW 74.45' Nail in sde 14" Maple NE 42.53' Nail in sde 12" Oak SSW 45.22' PK in sde fence post South 18.10' $\phi$ "X" West 125'+	B-1 capped re-rod. <u>N 1/4 Cor 6</u> Nail in sde 16" Oak SW 39.85' Nail in sde 14" Maple NW 20.45' Nail in sde 12" Poplar NNE 27.53' Nail in sde 16" Oak SE 48.15'
--	--	---


SIGNED BY Douglas W. Bonnema DATE December 26, 1978  
EXCEL ENGINEERING, INC.

SURVEYOR'S MICHIGAN REGISTRATION NO. 12579

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_  
MICHIGAN REGISTERED LAND SURVEYOR



SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_